# **TEMPICE 700**

Temperature below -10°C | Wet environments

## Reinforced Durability to push the limits of cold

# AAPA TOO TEMPICE BEN 382 ENSH 107 32222 OX

### EN388



3222X

EN511



02X

DEXTERITY EN 420:

5/5

# **SPECIFIC ADVANTAGES**



### Comfort

Stay dry when working in wet conditions



### Durability

• Coating 5 times as durable than standard gloves on the market



### **Productivity**

• Excellent grip when handling wet parts



### Food compliance

• Suitable for frozen, dry and some fatty foods use according to the French law of November 9th, 1994 and to the European Directive CEE 1935/2004



### **Guaranteed quality**

• Silicone free to prevent traces, defects on metal sheet and glass prior to painting



CAT.2

### Washability

• Washable until 5 cleaning cycles (see laundering and drying conditions)

### **INDUSTRIES**

- Local Authorities (Catering Services)
- Local Authorities (Roads and Highways)
- Local Authorities (Parks and Public Spaces)
- Local Authorities (Waste Collection and Processing)
- Other industries
- Transport, logistics

### **APPLICATIONS**

- Public park maintenance
- Maintaining the roads
- Waste collection
- Construction materials handling
- Maintenance in wet or cold environments
- Order preparation



# **TEMPICE 700**

Temperature below -10°C | Wet environments

# LEGENDS

EN388

**MECHANICAL HAZARDS** 



PERFORMANCE LEVELS (X = NOT TESTED)

3 2 2 2 X

O-4 O-5 O-4 O-4 A-F P

| Impact protection (optional)

| Cut resistance according to ISO |
| 13997 |
| Puncture resistance |
| Tear resistance |

EN511

Abrasion resistance

**COLD HAZARDS** 



PERFORMANCE LEVELS (X = NOT TESTED)

 $\frac{0}{0.4} \frac{2}{0.4} \frac{X}{0.4}$ 

| Water permeability | Contact cold resistance | Convective cold resistance

Blade cut resistance

# PRODUCT DETAILS

Interior finish	Knitted thermal protection
Exterior finish	Non-slip grip
Material	Nitrile GRIP&PROOF coating
Cuff characteristic	Knitted Cuff
Colors of the gloves	Black Blue
Length (cm)	24-27
Size	7 8 9 10
Surface resistance according to EN1149-1 (Value in palm area at 25% HR)	7.6E+9 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% HR)	3.5E+11 Ω

# LOGISTIC DETAILS

Packaging	1 pair/bag 12 pairs/bag
	72 pairs/carton

# **LEGISLATION**

- $\,$  This product is not classified hazardous according to the regulation (EC)  $\,$  n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation  $n^{\circ}$  1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/08/18/1671
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE

