# **ULTRANITRIL 480**

Prolonged contact (or immersion) | short wear

#### Ultra-long chemical protection

# SPECIFIC ADVANTAGES



#### Durability

• Longer service life: excellent mechanical resistance (abrasion, perforation)



#### **Productivity**

Good grip on slippery objects, due to the embossed texture



#### Skin protection

• Excellent protection during intensive handling of high-risk chemical products



#### **Guaranteed quality**

• Silicone free to prevent traces, defects on metal sheet and glass prior to painting



CHEMICAL PROTECTION **TYPE A** 

EN ISO 374-1

TYPE A

EN388



4102X

ISO 18889

**AJKOPT** 

CAT.3



0334

EN ISO 374-5



DEXTERITY EN 420:

5/5

#### **INDUSTRIES**

- Automotive/mechanical industry
- Chemical industry
- Other industries
- Agriculture sector

### **APPLICATIONS**

- Spray mixtures preparation
- Tank filling
- Application & spreading of pesticides
- Pesticides waste management
- Treatment equipment cleaning
- Treating/degreasing metals with aggressive
- Handling drums of chemical products
- Application of pesticides
- Cleaning of printing-press rollers
- Maintenance

Edit 05/05/2021



# **ULTRANITRIL 480**

Prolonged contact (or immersion) | short wear

## **LEGENDS**

**FN388** 

MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT

4 1 0 2 X 0-4 0-5 0-4 0-4 A-F Impact protection (optional) Cut resistance according to ISO 13997 Puncture resistance Tear resistance

EN ISO 374-1 TYPE A

**CHEMICAL RISKS** 



Abrasion resistance

A: Methanol

Blade cut resistance

J: n-Heptane

K: Sodium hydroxide 40%

O: Ammonia 25%

P: Hydrogen peroxide 30%

T: Formaldehyde 37%



#### PROTECTION FROM PESTICIDES

G2: Diluted & concentrated pesticides / Mechanical risk

ISO 18889

EN ISO 374-5





Protection against bacteria and fungi

## PRODUCT DETAILS

Interior finish	Chlorinated
Exterior finish	Embossed texture
Material	Nitrile
Cuff characteristic	Straight cuff
Colors of the gloves	Green
Length (cm)	46
Thickness (mm)	0.55
Size	7 8 9 10

## LOGISTIC DETAILS

Packaging	1 pair/bag 12 pairs/carton	
-----------	-------------------------------	--

#### **LEGISLATION**

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation no 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/16206/18/1069
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 Asqual 14 rue des Reculettes -75013 Paris -France

