

ULTRANE 500

Grip and skin protection for oily environments.

SPECIFIC ADVANTAGES

Durability

- Color adapted to dirty environements for a prolonged durability.
- Excellent abrasion resistance due to the nitrile coating

Productivity

• Grip and Proof coating ensures an excellent grip in oily environment. It also reduces muscle strain and boost productivity

Skin protection

- Oilproof, it repels oil penetration and reduce dermatitis
- Free of harmful substances: DMF Free

Guaranteed quality

• Silicone free to prevent traces, defects on metal sheet and glass prior to painting

Washability

 Washable 3 times at 40° without any alteration on performances* to extend lifespan, reduce costs and waste

Additional benefits

Available in vending machine packaging

INDUSTRIES

- Automotive/mechanical industry
- Mechanical industry
- Other industries
- Glass industry
- Agriculture sector

APPLICATIONS

- Handling glass sheets
- Re-entry tasks
- Cutting and stamping metal
- Maintenance in wet environments (water, oil, greases, hydrocarbons)
- Maintenance in wet environments
- Handling and sorting small, sharp parts
- Handling oily mechanical parts
- Handling sheet metal
- Machining parts using cutting oil





EN388



4121A

CAT.3



0075





X1XXXX

ISO 13997:

5 N

ISO 18889

DEXTERITY

EN 420: 5/5





MAPA SAS capital de 35.000.010 €



ULTRANE 500

LEGENDS

EN388

MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)

4 1 2 1 A

0-4 0-5 0-4 0-4 A-F P

| Impact protection (optional)

| Cut resistance according to ISO | 13997

| Puncture resistance | Tear resistance

EN407

Abrasion resistance

THERMAL RISKS (HEAT AND FIRE)



PERFORMANCE LEVELS (X = NOT TESTED)



Blade cut resistance

Resistance to large quantities of molten metal

Small splashes of molten metal

Radiant heat resistant
Convective heat resistance
Contact heat resistance
Limited flame spread



PROTECTION FROM PESTICIDES

GR: Re-entry tasks

ISO 18889

PRODUCT DETAILS

Interior finish	Seamless textile support
Gauge	13
Exterior finish	Ventilated back
Material	Nitrile GRIP&PROOF coating
Cuff characteristic	Knitted Cuff
Colour.s	Black
Size	6 7 8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	1.1Ε+10 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	4.4E+11 Ω

LOGISTIC DETAILS

Packaging	1 pair/bag 12 pairs/bag
	96 pairs/carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/09/18/1953
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0075 | CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE

* Tests carried out on unworn gloves (i.e. in new condition) which differs from the reality in the field.



RCS Nanterre 314 307 720

Edit 04/05/2023

