ALTO 265

Strong protection against aggressive concentrated detergents

CHEMICAL PROTECTION

TYPE B

EN388

1110X

EN ISO 374-1 TYPE B



EN ISO 374-5



CAT.3

DEXTERITY
EN 420:



0334

SPECIFIC ADVANTAGES

Comfort

Added comfort and absorption of prespiration, due to the cotton flock-lining



Productivity

Good handling of slippery objects, due to the embossed texture



Skin protection

Good resistance to many diluted acids

INDUSTRIES

- Mechanical industry
- Chemical industry
- Aeronautics industry

APPLICATIONS

- Work with composite materials (resins)
- Common handling Tasks
- Assembly of small, oil and grease free parts
- Minor maintenance Tasks

Edit 05/05/2021

ALTO 265

(LEGENDS)

EN388

MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)

1 1 0-4 0-5 0-4 0-4 A-F P | Impact protection (optional) | Cut resistance according to ISO 13997

EN ISO 374-1

Abrasion resistance

374-1 CHEMICAL RISKS

Tear resistance Blade cut resistance



K: Sodium hydroxide 40%

- P: Hydrogen peroxide 30%
- S: Hydrofluoric acid 40%

FN ISO 374-5

MICRO-ORGANISMS



Protection against bacteria and fungi

PRODUCT DETAILS

Interior finish	Flocked
Exterior finish	Embossed texture
Material	Natural latex
Cuff characteristic	Straight cuff
Colors of the gloves	Black

LOGISTIC DETAILS

Packaging	1 pair/bag 100 pairs/carton
	i o o pomio, o an o o i

LEGISLATION

- This product is not classified as hazardous according to the directive 1999/45/EC of the European Parliament and of the Council.
- This product does not contain any substances of very high concern according to the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/08/18/1640 EXT 01/08/18
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 Asqual 14 rue des Reculettes -75013 Paris -France

Edit 05/05/2021