ULTRANITRIL 485

Frequent contact | intermittent wear


Good sensitivity for standard chemical protection

SPECIFIC ADVANTAGES Comfort

• Excellent dexterity, due to the suppleness of the glove



Good grip on slippery objects, due to the embossed texture





CHEMICAL PROTECTION **TYPE B**

EN388



3101X

ISO 18889

EN ISO 374-1 TYPE B



JKOPT

CAT.3

0334

DEXTERITY EN 420:

5/5

EN ISO 374-5

INDUSTRIES

- Automotive/mechanical industry
- Chemical industry
- Other industries
- Agriculture sector

APPLICATIONS

- Spray mixtures preparation
- Pesticides handling
- Tank filling
- Application & spreading of pesticides
- Pesticides waste management
- Treatment equipment cleaning
- Machining parts using cutting oil
- Manufacture and application of paints and varnishes
- Application of phytosanitary products
- Maintenance



ULTRANITRIL 485

Frequent contact | intermittent wear


LEGENDS

FN388

MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT




EN ISO 374-1 TYPE B

Abrasion resistance

CHEMICAL RISKS

J: n-Heptane

Blade cut resistance



P: Hydrogen peroxide 30% T: Formaldehyde 37%



PROTECTION FROM PESTICIDES

G2: Diluted & concentrated pesticides / Mechanical risk

ISO 18889

EN ISO 374-5



MICRO-ORGANISMS

Protection against bacteria and fungi

PRODUCT DETAILS

Interior finish	Flocked
Exterior finish	Embossed texture
Material	Nitrile
Cuff characteristic	Straight cuff
Colors of the gloves	Green
Length (cm)	31
Thickness (mm)	0.34
Size	7 8 9 10

LOGISTIC DETAILS

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation no 1907/2006 of the European Parliament and of the Council (REACH).
- UE certificate CE type examination certificate: type 0075/014/162/10/18/2079
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 Asqual 14 rue des Reculettes -75013 Paris -France

Edit 05/05/2021