



Cut protection

KRYTECH 585

Moderate risk - ISO C

Enhanced safety, comfort and durability with Grip & Proof Technology



CUT PROTECTION
LEVEL C

SPECIFIC ADVANTAGES



Cut protection

- Optimal cut resistance



Comfort

- A seamless plaited glove and an optimized coating covering for a maximum comfort, dexterity and flexibility.



Durability

- Optimal durability that offers better productivity and optimizes your costs



Practical

- Cut level easy to identify thanks to the marking on the back of the glove.

INDUSTRIES

- Automotive/mechanical industry
- Food industry
- Construction Industry (Metalworkers/Locksmiths)
- Other industries
- Plastics industry
- Manufacturing

APPLICATIONS

- Finishing sharp parts
- Handling metal parts
- Handling parts post-press
- Machining parts using cutting oil
- Handling and installing metal structures
- Maintenance and work in cold stores
- Handling heavy parts with cut risk
- Cutting & stamping heavy metal sheets
- Maintenance in wet or cold environments
- Road works in cold conditions



EN388

4X42C

CAT.2



ISO 13997:

13 N

DEXTERITY
EN 420:

5/5





Cut protection

KRYTECH 585

Moderate risk - ISO C

LEGENDS

| EN388 | | MECHANICAL HAZARDS | |
|-------------------------------------|-----|--------------------|---------------------------------------|
| | | | |
| PERFORMANCE LEVELS (X = NOT TESTED) | | | |
| 4 | X | 4 | 2 C |
| 0-4 | 0-5 | 0-4 | 0-4 A-F P |
| | | | Impact protection (optional) |
| | | | Cut resistance according to ISO 13997 |
| | | | Puncture resistance |
| | | | Tear resistance |
| | | | Blade cut resistance |
| | | | Abrasion resistance |

PRODUCT DETAILS

| | |
|--|---|
| Interior finish | Seamless textile support from HDPE fibres |
| Gauge | 15 |
| Exterior finish | Ventilated back |
| Material | Nitrile GRIP&PROOF coating |
| Cuff characteristic | Knitted Cuff |
| Colors of the gloves | Black Grey |
| Length (cm) | 24-30 |
| Size | 7 8 9 10 11 |
| Surface resistance according to EN1149-1 (Value in palm area at 25% HR) | 2.7E+10 Ω |
| Vertical resistance according to EN1149-2 (Value in palm area at 25% HR) | 3.0E+11 Ω |

LOGISTIC DETAILS

| | |
|-----------|---|
| Packaging | 1 pair/bag 12 pairs/bag 48 pairs/carton |
|-----------|---|

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/05/18/0907
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE

Edit 05/05/2021