



Chemical protection

# ULTRANITRIL 381

Frequent contact | ultra-comfort wear

## Maximum comfort and chemical protection



CHEMICAL PROTECTION  
**TYPE A**

### SPECIFIC ADVANTAGES

#### Thermal protection

- Added comfort and thermal insulation, due to the cotton-knit lining



#### Comfort

- Extremely supple, due to the unique Mapa multi-layer process



#### Productivity

- Good grip on slippery objects, due to the embossed texture



#### Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting



#### Additional benefits

- Available in vending machine packaging

### INDUSTRIES

- Automotive/mechanical industry
- Chemical industry
- Other industries
- Agriculture sector

### APPLICATIONS

- Spray mixtures preparation
- Pesticides handling
- Tank filling
- Application & spreading of pesticides
- Pesticides waste management
- Treatment equipment cleaning
- Automotive assembly
- Part degreasing
- Surface treatment
- Chemical product blending



EN388  
3111A

EN ISO 374-1  
TYPE A



JKLOPT



EN ISO 374-5  
CAT.3



0334



EN407  
X1XXXX



G2  
ISO 18889

DEXTERITY  
EN 420:

5/5



Chemical protection

# ULTRANITRIL 381

Frequent contact | ultra-comfort wear

## LEGENDS

<b>EN388</b>	<b>MECHANICAL HAZARDS</b>
	<b>PERFORMANCE LEVELS (X = NOT TESTED)</b>
<b>3 1 1 1 A</b>	
0-4 0-5 0-4 0-4 A-F P	
	Impact protection (optional)
	Cut resistance according to ISO 13997
	Puncture resistance
	Tear resistance
	Blade cut resistance
	Abrasion resistance

<b>EN407</b>	<b>THERMAL RISKS (HEAT AND FIRE)</b>
	<b>PERFORMANCE LEVELS (X = NOT TESTED)</b>
<b>X 1 X X X X</b>	
0-4 0-4 0-4 0-4 0-4 0-4	
	Resistance to large quantities of molten metal
	Resistance to small drops of molten metal
	Radiant heat resistant
	Convective heat resistance
	Contact heat resistance
	Burning behaviour

<b>EN ISO 374-1</b>	<b>CHEMICAL RISKS</b>
<b>TYPE A</b>	J: n-Heptane
	K: Sodium hydroxide 40%
	L: Sulphuric acid 96%
	O: Ammonia 25%
	P: Hydrogen peroxide 30%
	T: Formaldehyde 37%

	<b>PROTECTION FROM PESTICIDES</b>
<b>G2</b>	G2: Diluted & concentrated pesticides / Mechanical risk
<b>ISO 18889</b>	

<b>EN ISO 374-5</b>	<b>MICRO-ORGANISMS</b>
	Protection against bacteria and fungi

## PRODUCT DETAILS

Interior finish	Textile support Mapa Technology
Exterior finish	Embossed texture
Material	Nitrile
Cuff characteristic	Feston Cuff
Colors of the gloves	Green
Length (cm)	36
Thickness (mm)	0.95
Size	7 8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% HR)	7.6E+10 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% HR)	2.9E+10 Ω

## LOGISTIC DETAILS

Packaging	12 pairs/bag 72 pairs/carton
-----------	---------------------------------

## LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/08/18/1663
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France