

ULTRANE 510

Optimal comfort, breathability and durability

S CAN STATE OF THE PARTY OF THE

EN388



CAT.2



DEXTERITY EN 420:

5/5

OEKO-TEX ® CONFIDENCE IN TEXTILES STANDARD 100 CQ 979/2 IFTH Tested for harmful substances. www.oeko-lex.com/standard100

SPECIFIC ADVANTAGES



Comfort

- Breathable coating to have better comfort in use
- Excellent dexterity due to the precise fit



Durable for a long-wear



- Free of harmful substances: STANDARD 100 by OEKO-TEX®
- Free of harmful substances: DMF Free



• Silicone free to prevent traces, defects on metal sheet and glass prior to painting

INDUSTRIES

- Automotive/mechanical industry
- Other industries
- Plastics industry
- Manufacturing
- Industrial maintenance

APPLICATIONS


- Assembly of small parts
- Automotive assembly
- Fitting small screws and fasteners
- Mechanical maintenance
- Precision assembly
- Precision mechanical work
- Packaging
- Warehousing and receipt of goods
- Post-injection material removal

Edit 05/05/2021



ULTRANE 510

LEGENDS



PRODUCT DETAILS

Interior finish	Seamless textile support
Exterior finish	Ventilated back
Material	Water-based polymer
Cuff characteristic	Knitted Cuff
Colors of the gloves	Black Green
Length (cm)	22-27
Size	6 7 8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% HR)	1.0E+11 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% HR)	3.2E+11 Ω

LOGISTIC DETAILS

	1 pair/bag 12 pairs/bag 96 pairs/carton
--	---

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) $n^{\circ}1272/2008$ of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/01/19/0133
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE

