



Cut protection

# KRYTECH 380

Low risk - ISO B

Best cut protective glove for heavy duty work in oily environments



CUT PROTECTION  
**LEVEL B**

EN388



4344B

EN407



X1XXXX

ISO 13997:

7.6 N

CAT.2



## SPECIFIC ADVANTAGES



### Comfort

- Large cuff: Easy to put and remove - Reduction of RSI (musculoskeletal symptoms) risks
- Large cuff and cotton inside: good perspiration management



### Durability

- Longer service life: excellent mechanical resistance (abrasion, perforation)



### Productivity

- Excellent grip for better productivity



### Skin protection

- Skin protected on palm and knuckle in oily/wet conditions



### Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

## INDUSTRIES

- Automotive/mechanical industry
- Mechanical industry

## APPLICATIONS

- Handling parts post-press
- Pressing metal, handling metal sheets
- Cutting and stamping metal
- Metal stamping in very oily environments



Cut protection

# KRYTECH 380

Low risk - ISO B

## LEGENDS

**EN388 MECHANICAL HAZARDS**

**PERFORMANCE LEVELS (X = NOT TESTED)**

<b>4</b>	<b>3</b>	<b>4</b>	<b>4</b>	<b>B</b>	
0-4	0-5	0-4	0-4	A-F	P
					Impact protection (optional)
					Cut resistance according to ISO 13997
					Puncture resistance
					Tear resistance
					Blade cut resistance
					Abrasion resistance

**EN407 THERMAL RISKS (HEAT AND FIRE)**

**PERFORMANCE LEVELS (X = NOT TESTED)**

<b>X</b>	<b>1</b>	<b>X</b>	<b>X</b>	<b>X</b>	<b>X</b>
0-4	0-4	0-4	0-4	0-4	0-4
					Resistance to large quantities of molten metal
					Resistance to small drops of molten metal
					Radiant heat resistant
					Convective heat resistance
					Contact heat resistance
					Burning behaviour

## PRODUCT DETAILS

Interior finish	Seamless textile support from HDPE and cotton fibres
Exterior finish	Ventilated back
Material	Nitrile GRIP&PROOF coating
Cuff characteristic	Large safety cuff
Colors of the gloves	Black Grey
Length (cm)	24-26
Size	8 9 10
Surface resistance according to EN1149-1 (Value in palm area at 25% HR)	8.6E+8 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% HR)	1.8E+8 Ω

## LOGISTIC DETAILS

Packaging	1 pair/bag 6 pairs/bag 48 pairs/carton
-----------	--

## LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/08/14/0760
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE