TEMPDEX 720

Temperature below 150°C | Dry environments

Dexterity and resistance to cuts for optimised thermal protection

SPECIFIC ADVANTAGES



Cut protection

Knitted aramide fibres ensures protection from cuts



Thermal protection

Comfort and insulation of the interior terry-cloth



• Longer service life: good abrasion resistance



Special nitrile Grip coating facilitates work in moderately oily environments



• Free of harmful substances: DMF Free



• Silicone free to prevent traces, defects on metal sheet and glass prior to painting

LEVEL B



4X43B

EN407

CUT PROTECTION

CATEGORY 2



X2XXXX

ISO 13997:

DEXTERITY

7 N

EN ISO 21420: 5/5

INDUSTRIES

- Mechanical industry
- Other industries
- Rubber industry

APPLICATIONS

- Vulcanization, demoulding, forming, etc.
- Working with hot, sharp and oily parts
- Handling of hot piping
- Handling of hot steel after welding
- Handling of moulds in the ceramic industry

Edit 22/07/2024

TEMPDEX 720

Temperature below 150°C | Dry environments

(LEGENDS)

PERFORMANCE LEVELS (X = NOT TESTED) 4 X 4 3 B O-4 O-5 O-4 O-4 A-F P | Impact protection (optional) | Cut resistance according to ISO 13997 | Puncture resistance | | Blade cut resistance | | Abrasion resistance |

EN407

THERMAL RISKS (HEAT AND FIRE)



Limited flame spread

PERFORMANCE LEVELS (X = NOT TESTED)

| _ | | | TEST | ED) | | | |
|------------|-----|-----|---|-----|--|--|--|
| <u>X</u> : | 2 | X | X | X | X | | |
| 0-4 0 | -4 | 0-4 | 0-4 | 0-4 | 0-4 | | |
| | | | | | Resistance to large quantities of molten metal | | |
| | | | | Sn | nall splashes of molten metal | | |
| | Con | | Radiant heat resistant Convective heat resistance act heat resistance | | | | |

PRODUCT DETAILS

| Interior finish | Knitted thermal protection |
|---|----------------------------|
| Gauge | 10 |
| Exterior finish | Dots |
| Material | Nitrile |
| Cuff characteristic | Knitted Cuff |
| Colour.s | Black Orange |
| European sizes | 7 9 11 |
| Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity) | 1.6E+10 Ω |
| Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity) | 7.5E+11 Ω |

LOGISTIC DETAILS

| Packaging | 1 pair/bag 72 pairs/carton |
|-----------|-------------------------------|
|-----------|-------------------------------|

LEGISLATION

- $\,$ This product is not classified hazardous according to the regulation (EC) $\,$ n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/09/19/2717 update 02-16/04/2024
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE

Edit 22/07/2024