

FLUOTECH 468

short wear

Tactile sensitivity with wear-indicator

MAPA 468 FLUGTICE TO THE PARTY OF THE PARTY

CHEMICAL PROTECTION

TYPE A

EN ISO 374-1

EN388



TYPE A ADEFGJLMNO

CATEGORY 3

DEXTERITY



0334

EN420: 5/5

EN ISO 374-5

SPECIFIC ADVANTAGES



Comfort

 Excellent flexibility and thickness optimization, due to the Mapa multi-layer technology: good dexterity and comfort



Durability

• Nitrile inner layer: excellent mechanical resistance and a longer service life



Guaranteed quality

• Silicone free to prevent traces, defects on metal sheet and glass prior to painting



Practical

• Green inner layer: wear-indicator for greater user safety

INDUSTRIES

- Mechanical industry
- Chemical industry
- Other industries

APPLICATIONS

- Metal degreasing and etching
- Chemical treatments (solvents)
- Galvanoplasty
- Handling and transporting chemicals (solvents)
- Manufacturing paints and varnishes
- Resin and adhesive manufacturing
- Petrochemical refining
- Printing
- Site pollution control

FLUOTECH 468

short wear


LEGENDS

EN388

MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)



EN ISO 374-1

TYPE A

CHEMICAL RISKS

- A: Methanol D: Dichloromethane
- E: Carbon Disulfide
- F: Toluene
- G: Diethylamine
- J: n-Heptane
- L: Sulphuric acid 96%
- M: Nitric acid 65%
- N: Acetic acid 99%
- O: Ammonia 25%

EN ISO 374-5



MICRO-ORGANISMS

Protection against bacteria and fungi

PRODUCT DETAILS

Interior finish	Chlorinated
Exterior finish	Smooth
Material	Fluoroelastomer
Cuff characteristic	Feston Cuff
Colour.s	Black
Length (cm)	30
Thickness (mm)	0.51
European sizes	8 9 10

LOGISTIC DETAILS

Packaging	1 pair/carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/01/19/0326
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 Asqual 14 rue des Reculettes -75013 Paris -France

Edit 25/07/2024