

FLUOTECH 344

continous wear

Comfort and flexibility for extended wear

Måpa 344 Ruote E

CHEMICAL PROTECTION

TYPE A

EN388



3121X

EN407



EN ISO 374-1



TYPE A ACDEFGJLMN

CATEGORY 3



0334



DEXTERITY

EN ISO 21420: 2/5

SPECIFIC ADVANTAGES

Comfort

- Excellent comfort for long tasks, due to the cotton-knit interior
- Freedom of movement: good glove flexibility



• High mechanical resistance and long service life, due to textile support



 Silicone free to prevent traces, defects on metal sheet and glass prior to painting

INDUSTRIES

- Mechanical industry
- Chemical industry
- Other industries

APPLICATIONS

- Metal degreasing and etching
- Chemical treatments (solvents)
- Galvanoplasty
- Handling and transporting chemicals (solvents)
- Manufacturing paints and varnishes
- Resin and adhesive manufacturing
- Emergency interventions on chemical accidents
- Petrochemical refining
- Printing
- Site pollution control

Edit 25/07/2024

FLUOTECH 344

continous wear

LEGENDS

EN388

MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT

Impact protection (optional) Cut resistance according to ISO 13997 Puncture resistance Tear resistance Blade cut resistance


EN407

Abrasion resistance

THERMAL RISKS (HEAT AND FIRE)



PERFORMANCE LEVELS (X = NOT



EN ISO 374-1

Limited flame spread



A: Methanol

- **CHEMICAL RISKS** C: Acetonitrile
- D: Dichloromethane
- E: Carbon Disulfide
- F: Toluene
- G: Diethylamine
- J: n-Heptane
- L: Sulphuric acid 96%
- M: Nitric acid 65%
- N: Acetic acid 99%

EN ISO 374-5



MICRO-ORGANISMS

Protection against bacteria and fungi

PRODUCT DETAILS

Interior finish	Textile support
Exterior finish	Smooth
Material	Fluoroelastomer
Cuff characteristic	Feston Cuff
Colour.s	Black
Length (cm)	37
Thickness (mm)	1.6
European sizes	9 10
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	2.7Ε+10 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	4.3E+10 Ω

LOGISTIC DETAILS

 1 pair/bag
1 pair/carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation no 1907/2006 of the European Parliament and of the Council (REACH).
- type certificate or CE type examination certificate: 0075/014/162/02/19/0479
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 Asqual 14 rue des Reculettes -75013 Paris -France

