ULTRANITRIL 381

Frequent contact | ultra-comfort wear

Maximum comfort and chemical protection

MÅPA 381 ULTRANTER WE WE

CHEMICAL PROTECTION

TYPE A

EN388



3111A



X1XXXX

EN ISO 374-1



TYPE A AJKLOPT

CATEGORY 3

EN ISO 374-5



0334

DEXTERITY
EN ISO 21420:
5/5

ISO 18889

SPECIFIC ADVANTAGES



Thermal protection

Added comfort and thermal insulation, due to the cotton-knit lining



Comfort

• Extremely supple, due to the unique Mapa multi-layer process



Productivity

Good grip on slippery objects, due to the embossed texture



Additional benefits

Available in vending machine packaging

INDUSTRIES

- Automotive/mechanical industry
- Chemical industry
- Other industries
- Agriculture sector

APPLICATIONS

- Spray mixtures preparation
- Pesticides handling
- Tank filling
- Application & spreading of pesticides
- Pesticides waste management
- Treatment equipment cleaning
- Automotive assembly
- Part degreasing
- Surface treatment
- Chemical product blending

Edit 15/08/2024

ULTRANITRIL 381

Frequent contact | ultra-comfort wear


LEGENDS

EN388

MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)




EN407

THERMAL RISKS (HEAT AND FIRE)



PERFORMANCE LEVELS (X = NOT TESTED)



Radiant heat resistant
Convective heat resistance
Contact heat resistance
Limited flame spread

EN ISO 374-1



CHEMICAL RISKS A: Methanol

- J: n-Heptane
- K: Sodium hydroxide 40%
- L: Sulphuric acid 96%
- O: Ammonia 25%
- P: Hydrogen peroxide 30%
- T: Formaldehyde 37%



PROTECTION FROM PESTICIDES

G2: Diluted & concentrated pesticides / Mechanical risk

ISO 18889

EN ISO 374-5

MICRO-ORGANISMS



Protection against bacteria and fungi

PRODUCT DETAILS

Interior finish	Textile support Mapa Technology
Exterior finish	Embossed texture
Material	Nitrile
Cuff characteristic	Feston Cuff
Colour.s	Green
Length (cm)	36
Thickness (mm)	0.95
European sizes	7 8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	7.6E+10 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	2.9E+10 Ω

LOGISTIC DETAILS

Packaging	12 pairs/bag
	72 pairs/carton

LEGISLATION

- $\,$ This product is not classified hazardous according to the regulation (EC) $\,$ n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/08/18/1663
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 Asqual 14 rue des Reculettes -75013 Paris -France

