



Chemical protection

MUCAMBO PRO 250

Flocked | intermittent wear

Excellent comfort and dexterity



CHEMICAL PROTECTION
TYPE B

EN388



1100X

EN ISO 374-1



TYPE B
KLMOP

SPECIFIC ADVANTAGES



Comfort

- Excellent dexterity thanks to the flexibility of natural latex



Durability

- High mechanical strength
- Excellent durability



Productivity

- Reinforced grip for good handling
- Embossed texture provides excellent grip

INDUSTRIES

- Mechanical industry
- Construction Industry (Masons / Plasterers)
- Construction Industry (Painters/Decorators)
- Construction Industry (Carpenters/Joiners)
- Ceramic and plastics industry
- Civil engineering

APPLICATIONS

- Preparing and pouring mortar and cement
- Cleaning tools
- Plastering
- Cleaning
- Applying finishes
- Laying wood, panelling or moulding
- Assembly
- Handling of composite materials after heat processing
- Handling
- Assembly of small, oil and grease free parts



Chemical protection

MUCAMBO PRO 250

Flocked | intermittent wear

LEGENDS

EN388	MECHANICAL HAZARDS
	PERFORMANCE LEVELS (X = NOT TESTED)
1 1 0 0 X	
0-4 0-5 0-4 0-4 A-F P	
	Impact protection (optional)
	Cut resistance according to ISO 13997
	Puncture resistance
	Tear resistance
	Blade cut resistance
	Abrasion resistance
EN ISO 374-1	CHEMICAL RISKS
	K: Sodium hydroxide 40%
TYPE B	L: Sulphuric acid 96%
	M: Nitric acid 65%
	O: Ammonia 25%
	P: Hydrogen peroxide 30%

PRODUCT DETAILS

Interior finish	Flocked
Exterior finish	Embossed texture
Material	Natural latex
Cuff characteristic	Straight cuff
Colour.s	Green
Length (cm)	31-31
European sizes	6 7 8 9

LOGISTIC DETAILS

Packaging	1 pair/bag 10 pairs/bag 100 pairs/carton
-----------	--

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain any substances of very high concern according to the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: CA: 2429 NBR 13393/95