

# KRYTECH 576

High-performance protection for intricate handling in reasonably clean environments



## SPECIFIC ADVANTAGES



### Cut protection

- Optimal cut resistance: level 5 (ANSI Cut 4)



### Comfort

- Excellent dexterity due to the precise fit
- Added comfort and flexibility



### Skin protection

- Contains traces of DMF in compliance with occupational exposure limits

## INDUSTRIES

- Automotive/mechanical industry
- Local Authorities (Technical Maintenance)
- Construction Industry (Roofers/Tilers/Glazers)
- Plastics industry

## APPLICATIONS

- Handling and fitting windows
- Post-injection material removal
- Assembly of thin metal sheets
- Finishing sharp parts
- Handling metal parts
- Maintenance work with risk of cuts

CUT PROTECTION  
**LEVEL D**

EN388



4X42D

ANSI CUT



CATEGORY 2





DEXTERITY

EN420:  
5/5

WARNING:  
Cancer

## LEGENDS

<b>EN388</b>	<b>MECHANICAL HAZARDS</b>
	<b>PERFORMANCE LEVELS (X = NOT TESTED)</b>
<b>4 X 4 2 D</b>	
0-4 0-5 0-4 0-4 A-F P	
	Impact protection (optional)
	Cut resistance according to ISO 13997
	Puncture resistance
	Tear resistance
	Blade cut resistance
	Abrasion resistance
<b>ANSI CUT</b>	<b>CUT RESISTANCE</b>
	A4 ≥ 1500 G

## PRODUCT DETAILS

Interior finish	Seamless textile support from HDPE fibers
Gauge	13
Exterior finish	Ventilated back
Material	Polyurethane
Cuff characteristic	Knitted Cuff
Colour.s	Grey
Length (inches)	8.5-10.5"

## LOGISTIC DETAILS

Packaging	1 pair/bag 12 pairs/bag 96 pairs/carton
-----------	---

## LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain any substances of very high concern according to the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/01/19/0137
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE