

# **ULTRANE 525**

Grip assured, skin protected up to knuckle and unbeatable fingertip sensitivity in oily environments.

## **SPECIFIC ADVANTAGES**



#### Comfort

Unbeatable fingertip sensitivity



#### Durability

Excellent abrasion resistance due to the nitrile coating



#### **Productivity**

• Grip and Proof coating ensures an excellent grip in oily environment. It also reduces muscle strain and boost productivity



#### Skin protection

- Oilproof, repels oil penetration and reduce dermatitis
- Free of harmful substances: DMF Free



#### **Guaranteed quality**

• Silicone free to prevent traces, defects on metal sheet and glass prior to painting



#### Washability

• Washable 3 times at 40°, to extend lifespan, reduce costs and waste



### Care for the environment

- Optimised individual packaging to limit plastic waste
- Recycled material in the packaging: 30 %



EN388



4121A



**GRIP & PROOF** 

TECHNOLOGY



X1XXXX



**CATEGORY 3** 

ISO 13997:

4.9 N

**ANSI CUT** 



0334

DEXTERITY

EN ISO 21420: 5/5



## **INDUSTRIES**

- Automotive/mechanical industry
- Mechanical industry
- Local Authorities (Technical Maintenance)
- Glass industry
- Agriculture sector

### **APPLICATIONS**

- Handling glass sheets
- Re-entry tasks
- Handling and sorting small, sharp parts
- Handling oily mechanical parts
- Handling sheet metal
- Machining parts using cutting oil
- Assembly of small oily parts
- Maintenance in wet environments (water, oil, greases, hydrocarbons)
- Small general maintenance jobs





# **ULTRANE 525**

## LEGENDS

EN388

**MECHANICAL HAZARDS** 



PERFORMANCE LEVELS (X = NOT TESTED)

4 1 2 1 A

0-4 0-5 0-4 0-4 A-F P

| Impact protection (optional)

| Cut resistance according to ISO | 13997


| Puncture resistance | Tear resistance | Blade cut resistance | Abrasion resistance

EN407

THERMAL RISKS (HEAT AND FIRE)



PERFORMANCE LEVELS (X = NOT TESTED)



Radiant heat resistant
Convective heat resistance
Contact heat resistance
Limited flame spread



PROTECTION AGAINST PESTICIDES

GR: Re-entry tasks

ISO 18889

ANSI CUT

CUT RESISTANCE A1 ≥ 200 G

CUT

FOOD CONTACT US (FDA)

## PRODUCT DETAILS

Interior finish	Seamless textile support
Gauge	13
Exterior finish	Ventilated back
Material	Nitrile GRIP&PROOF coating
Cuff characteristic	Knitted Cuff
Colour.s	Black
European sizes	6 7 8 9 10 11

# LOGISTIC DETAILS

Packaging	1 pair/bag 12 pairs/bag
	96 pairs/carton

### LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/09/18/1953 Ext 02/09/18 Update 01-07/09/2023
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 Asqual 14 rue des Reculettes -75013 Paris -France

Edit 26/06/2024