

CHEMZOIL NL-339

Prolonged contact (or immersion) | continuous wear

Comfort and high-level chemical protection



) Thermal protection

SPECIFIC ADVANTAGES

• Thermal insulation from the cotton-knit lining for handling hot liquids



Durability

• Excellent mechanical resistance and longer service life, due to the textile support and the thickness of the glove



Productivity

Pebbled embossing, for better grip on wet and slippery objects



Skin protection

 Superior chemical resistance against acids and alkalis, such as concentrated hydrofluoric acid, oils, and greases, due to its 100% neoprene multi-layer construction



) Guaranteed quality

 Silicone free to prevent traces, defects on metal sheet and glass prior to painting





3121X

CATEGORY 3



EN ISO 374-1

CHEMICAL PROTECTION



TYPE A ABCJLMNS

DEXTERITY

EN ISO 21420: 5/5

EN407



X1XXXX

INDUSTRIES

- Mechanical industry
- Chemical industry

APPLICATIONS

- Surface treatment of metals (acids)
- Handling and transporting drums of chemical products
- Handling on alkylation units
- Hot, petrochemical product sampling
- Resin-working
- Site pollution control

Edit 24/07/2024

CHEMZOIL NL-339

Prolonged contact (or immersion) | continuous wear

LEGENDS

EN388

MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT


Impact protection (optional) Cut resistance according to ISO 13997 Puncture resistance Tear resistance Blade cut resistance Abrasion resistance

EN407

THERMAL RISKS (HEAT AND FIRE)



PERFORMANCE LEVELS (X = NOT



Contact heat resistance Limited flame spread

EN ISO 374-1



A: Methanol

B: Acetone C: Acetonitrile

CHEMICAL RISKS

J: n-Heptane

L: Sulphuric acid 96%

M: Nitric acid 65%

N: Acetic acid 99%

S: Hydrofluoric acid 40%

FOOD CONTACT US (FDA)

PRODUCT DETAILS

Interior finish	Textile support
Exterior finish	Pebbled
Material	Polychloroprene
Cuff characteristic	Feston Cuff
Colour.s	Black
Length (inches)	14.2"
Thickness (inches)	0.053" (53 mil)
European sizes	9 10
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	2.9Ε+11 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	1.2E+11 Ω

LOGISTIC DETAILS

Packaging	1 pair/bag 6 pairs/carton
	o pairs, cartori

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation no 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/12/18/2912
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 Asqual 14 rue des Reculettes -75013 Paris -France

