

SOLO PLUS 995

Latex | Easy going treatment

Optimal flexibility and dexterity

CHEMICAL PROTECTION **TYPE C**

EN ISO 374-1





EN ISO 374-5

CAT.3

0334

DEXTERITY EN 420: 5/5

SPECIFIC ADVANTAGES

Comfort

• Excellent dexterity from the suppleness of natural latex



Guaranteed quality

• Silicone free to prevent traces, defects on metal sheet and glass prior to painting



(Practical

- Easy to put on and take off
- Protection adapted to short duration usage

INDUSTRIES

- Health
- Laboratory

APPLICATIONS

- Common Tasks in hospitals and clinics
- Manufacturing of medicines
- Pharmaceutical preparation
- Research, analysis, handling of precision parts



SOLO PLUS 995

Latex | Easy going treatment

LEGENDS

EN ISO 374-1

CHEMICAL RISKS



TABEC

EN ISO 374-5



MICRO-ORGANISMS

Protection against bacteria and fungi

PRODUCT DETAILS

Interior finish	Easy donning treatment
Exterior finish	Smooth with pebbled fingertips
Material	Natural latex
Cuff characteristic	Rolled Cuff
Colour.s	Green
Length (inches)	9.7"
Thickness (inches)	0.004" (4 mil)
Size	6789
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	6.7E+12 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	4.9E+11 Ω

LOGISTIC DETAILS

Packaging 100 gloves/box 1000 gloves/carton	100 gloves/box 1000 gloves/carton
---	--------------------------------------

LEGISLATION

- $\,$ This product is not classified hazardous according to the regulation (EC) $\,$ n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/01/19/0041
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 Asqual 14 rue des Reculettes -75013 Paris -France

