STANSOLV AK-22 381

Frequent contact | ultra-comfort wear

Maximum comfort and chemical protection

CHEMICAL PROTECTION **TYPE A**

EN ISO 374-1

EN388



3111A

TYPE A **AJKLOPT**

EN407



X1XXXX



ISO 18889

DEXTERITY EN ISO 21420: 5/5



0334

EN ISO 374-5

SPECIFIC ADVANTAGES



Thermal protection

Added comfort and thermal insulation, due to the cotton-knit lining



Comfort

• Extremely supple, due to the unique Mapa multi-layer process



Productivity

Good grip on slippery objects, due to the embossed texture



Additional Benefits

Available in vending machine packaging



Care for the environment

- Plastic packaging optimized, Recycled packaging
- Recycled material in the packaging: 30 %

INDUSTRIES

- Automotive/mechanical industry
- Chemical industry
- Other industries
- Agriculture sector

APPLICATIONS

- Spray mixture preparation
- Pesticides handling
- Tank filling
- Application & spreading of pesticides
- Pesticides waste management
- Treatment equipment cleaning
- Automotive assembly
- Part degreasing
- Surface treatment
- Chemical product blending

STANSOLV AK-22 381

Frequent contact | ultra-comfort wear

LEGENDS

EN388

MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)

3 1 0-4 1 A A P P | Impact protection (optional)

Cut resistance according to ISO 13997

Puncture resistance | Tear resistance | Blade cut resistance

EN407

Abrasion resistance

THERMAL RISKS (HEAT AND FIRE)



PERFORMANCE LEVELS (X = NOT TESTED)

X 1 X X X X O-4 O-4 O-4 O-4 Resista

Resistance to large quantities of molten metal

Small splashes of molten metal

Radiant heat resistant
Convective heat resistance
Contact heat resistance
Limited flame spread

EN ISO 374-1



CHEMICAL RISKS A: Methanol

- J: n-Heptane
- K: Sodium hydroxide 40%
- L: Sulphuric acid 96%
- O: Ammonia 25%
- P: Hydrogen peroxide 30%
- T: Formaldehyde 37%



PROTECTION AGAINST PESTICIDES

G2: Diluted & concentrated pesticides / Mechanical risk

ISO 18889

EN ISO 374-5

MICRO-ORGANISMS

Protection against bacteria and fungi

FOOD CONTACT US (FDA)

PRODUCT DETAILS

Interior finish	Textile support Mapa Technology
Exterior finish	Embossed texture
Material	Nitrile
Cuff characteristic	Feston Cuff
Colour.s	Green
Length (inches)	14.2"
Thickness (inches)	0.037" (37 mil)
European sizes	7 8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	7.6E+10 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	2.9E+10 Ω

LOGISTIC DETAILS

Packaging	12 pairs/bag
	72 pairs/carton

LEGISLATION

- $\,$ This product is not classified hazardous according to the regulation (EC) $\,$ n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/08/18/1663
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 Asqual 14 rue des Reculettes -75013 Paris -France



Edit 18/09/2024