TEMPCOOK 476

Temperature below 150°C | Wet environments

Hygienic combined with effective thermal protection; 100% fluid-proof

SPECIFIC ADVANTAGES

Thermal protection

• Thermal protection up to 250°C* (* from 150°C, the product can get stiffer and color change may happen, without degrading glove efficiency.)



Durability

• Resistance to oils, greases and principal detergent products



Food compliance

• The white/cream colour coding meets the catering industry clothing standards



Guaranteed quality

• Silicone free to prevent traces, defects on metal sheet and glass prior to painting



CUT PROTECTION **LEVEL D**

EN ISO 374-5

EN388



TYPE A

EN ISO 374-1

AFGJOT

EN407



EN511 (COLD)

X2XXXX



EN 420: 1/5

DEXTERITY

INDUSTRIES

- Food industry
- Local Authorities (Catering) Services)
- Catering industry
- Bakeries

APPLICATIONS

- Removing dishes from warming ovens
- Removing hot dishes from dry or wet ovens
- Removing items from autoclaves and steam ovens
- Removing trays from ovens
- Pre-cooking

Edit 19/12/2022

TEMPCOOK 476

Temperature below 150°C | Wet environments

LEGENDS

FN388

MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT

Impact protection (optional) Cut resistance according to ISO 13997 Puncture resistance Tear resistance

EN407

Abrasion resistance

THERMAL RISKS (HEAT AND FIRE)



PERFORMANCE LEVELS (X = NOT



Blade cut resistance

Resistance to large quantities of molten metal

Small splashes of molten metal

Radiant heat resistant Convective heat resistance Contact heat resistance

EN511 (Cold)

Limited flame spread

COLD HAZARDS



PERFORMANCE LEVELS (X = NOT

Water permeability Contact cold resistance Convective cold resistance

EN ISO 374-1

CHEMICAL RISKS A: Methanol



TYPE A

F: Toluene G: Diethylamine

J: n-Heptane

O: Ammonia 25%

T: Formaldehyde 37%

EN ISO 374-5

MICRO-ORGANISMS



Protection against bacteria and fungi

ALIMENTARY US (FDA)

Edit 19/12/2022

PRODUCT DETAILS

Interior finish	Knitted thermal protection
Exterior finish	Embossed texture
Material	Nitrile
Colour.s	White
Length (inches)	17.7"
Size	7 9 10
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	1.6E+11 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	> 3E+13 Ω

LOGISTIC DETAILS

Packaging	1 pair/bag 6 pairs/carton
	o pairs, cartori

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation no 1907/2006 of the European Parliament and of the Council (REACH).
- type certificate or type examination certificate: 0075/014/162/04/19/1095 updated 01-11/10/2021
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE

