

ULTRANE 500

Grip and skin protection for oily environments.

A PA 500 ULTAANE EN 389 QUITA SO 1809 MONT STANDARD 100 BY VEID-ETS







4121A

CATEGORY 3



0334

EN407



X1XXXX

ISO 13997:

4.9 N

DEXTERITY EN ISO 21420: 5/5

ISO 18889



SPECIFIC ADVANTAGES

Durability

- Color adapted to dirty environements for a prolonged durability.
- Excellent abrasion resistance due to the nitrile coating



) Productivity

• Grip and Proof coating ensures an excellent grip in oily environment. It also reduces muscle strain and boost productivity



Skin protection

- Free of harmful substances: OEKO-TEX® STANDARD 100, DMF Free
- Oilproof, it repels oil penetration and reduce dermatitis



Guaranteed quality

• Silicone free to prevent traces, defects on metal sheet and glass prior to painting



Washability

• Washable 3 times at 40°, to extend lifespan, reduce costs and waste



Additional benefits

Available in vending machine packaging



Care for the environment

- Optimised individual packaging to limit plastic waste
- Recycled material in the packaging: 30 %

INDUSTRIES

- Automotive/mechanical industry
- Other industries
- Glass industry
- Agriculture sector

APPLICATIONS

- Handling glass sheets
- Re-entry tasks
- Handling and sorting small, sharp parts
- Handling oily mechanical parts
- Handling sheet metal
- Machining parts using cutting oil
- Cutting and stamping metal
- Maintenance in wet environments (water, oil, greases, hydrocarbons)
- Maintenance in wet environments





ULTRANE 500


LEGENDS

EN388

MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT




EN407

THERMAL RISKS (HEAT AND FIRE)



PERFORMANCE LEVELS (X = NOT





PROTECTION FROM PESTICIDES

GR: Re-entry tasks

ISO 18889

PRODUCT DETAILS

Interior finish	Seamless textile support
Gauge	13
Exterior finish	Ventilated back
Material	Nitrile GRIP&PROOF coating
Cuff characteristic	Knitted Cuff
Colour.s	Black
European sizes	6 7 8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	1.1E+10 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	4.4E+11 Ω

LOGISTIC DETAILS

Packaging	1 pair/bag 12 pairs/bag
	96 pairs/carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation no 1907/2006 of the European Parliament and of the Council (REACH).
- CE examination certificate or type certificate: 0075/014/162/09/18/1953 Update 01-07/09/2023
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 Asqual 14 rue des Reculettes -75013 Paris -France

