



Chemical protection

# ALTO 415

Frequent contact | intermittent wear

## Fine touch for light chemical protection



CHEMICAL PROTECTION  
**TYPE B**

EN388



1011X

EN ISO 374-1



TYPE B  
KMT

EN ISO 374-5



EN 421



CATEGORY 3



0334

DEXTERITY

EN420:  
5/5

### SPECIFIC ADVANTAGES



#### Comfort

- Tactile sensitivity, due to the gloves reduced thickness
- Added comfort and absorption of perspiration, due to the cotton flock-lining



#### Productivity

- Good grip, due to the non-slip embossing



#### Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting



#### Care for the environment

- Optimised individual packaging to limit plastic waste
- Recycled material in the packaging: 30 %

### INDUSTRIES

- Automotive/mechanical industry
- Aeronautics industry
- Other industries

### APPLICATIONS

- Work with composite materials (resins)
- Spray-painting
- Industrial cleaning, maintenance




Chemical protection

# ALTO 415

Frequent contact | intermittent wear

## LEGENDS

**EN388** **MECHANICAL HAZARDS**



**PERFORMANCE LEVELS (X = NOT TESTED)**

**1 0 1 1 X**

0-4 0-5 0-4 0-4 A-F P

Impact protection (optional)

Cut resistance according to ISO 13997

Puncture resistance


Tear resistance

Blade cut resistance

Abrasion resistance

---

**EN ISO 374-1** **CHEMICAL RISKS**



K: Sodium hydroxide 40%


M: Nitric acid 65%

T: Formaldehyde 37%

**TYPE B**


---

**EN 421** **RADIOACTIVE CONTAMINATION**




---

**EN ISO 374-5** **MICRO-ORGANISMS**



Protection against bacteria and fungi

## PRODUCT DETAILS

Interior finish	Flocked
Exterior finish	Embossed texture
Material	Polychloroprene and natural latex
Cuff characteristic	Straight cuff
Colour.s	Black
Length (cm)	32
Thickness (mm)	0.6
European sizes	6 7 8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	6.5E+12 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	6.6E+12 Ω

## LOGISTIC DETAILS

Packaging	1 pair/bag 10 pairs/bag 100 pairs/carton
-----------	--

## LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/08/18/1643
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France