

MUCAMBO PRO 250

Flocked | intermittent wear

Excellent comfort and dexterity



CHEMICAL PROTECTION **TYPE B**

EN388



1100X

EN ISO 374-1



KLMOP

SPECIFIC ADVANTAGES

Comfort

• Excellent dexterity thanks to the flexibility of natural latex



Durability

- High mechanical strength
- Excellent durability



Productivity

- Reinforced grip for good handling
- Embossed texture provides excellent grip

INDUSTRIES

- Mechanical industry
- Construction Industry (Masons / Plasterers)
- Construction Industry (Painters/Decorators)
- Construction Industry (Carpenters/Joiners)
- Ceramic and plastics industry
- Civil engineering

APPLICATIONS

- Handling of composite materials after heat processing
- Handling
- Preparing and pouring mortar and cement
- Cleaning tools
- Plastering
- Cleaning
- Applying finishes
- Laying wood, panelling or moudling
- Assembly
- Assembly of small, oil and grease free parts

Edit 30/06/2023

MUCAMBO PRO 250

Flocked | intermittent wear

LEGENDS

EN388

MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT

Impact protection (optional) Cut resistance according to ISO 13997 Puncture resistance Tear resistance

EN ISO 374-1

CHEMICAL RISKS

Blade cut resistance

Abrasion resistance



K: Sodium hydroxide 40% L: Sulphuric acid 96% M: Nitric acid 65%

O: Ammonia 25%

P: Hydrogen peroxide 30%

PRODUCT DETAILS

Interior finish	Flocked
Exterior finish	Embossed texture
Material	Natural latex
Cuff characteristic	Straight cuff
Colour.s	Green
Length (cm)	31-31
Thickness (mm)	0.50 mm
European sizes	6789

LOGISTIC DETAILS

Packaging	1 pair/bag 10 pairs/bag
	100 pairs/carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain any substances of very high concern according to the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: CA: 2429 NBR 13393/95

Edit 30/06/2023