

KRYTECH 580

Low risk - ISO B

Cut, Grip and Skin Protection for oily environments

MAPA 580 KRYTCH BE LEVEL STATE OF THE STA



CUT PROTECTION LEVEL B

EN388



4X42B
CATEGORY 3



EN407



X1XXXX

ISO 13997:

6 N



ISO 18889

DEXTERITY

EN ISO 21420: 5/5



SPECIFIC ADVANTAGES

Durability

Excellent abrasion resistance due to the nitrile coating



Productivity

 Grip and Proof coating ensures an excellent grip in oily environment. It also reduces muscle strain and boost productivity

Skin protection

- Free of harmful substances: OEKO-TEX® STANDARD 100, DMF Free
- Oilproof, it repels oil penetration and reduce dermatitis



Guaranteed quality

• Silicone free to prevent traces, defects on metal sheet and glass prior to painting



Care for the environment

- 95 gr CO₂ of carbon footprint reduction ¹
- Recycled material in the glove: 15 %
- Recycled material in the liner: 25 %
- Optimised individual packaging to limit plastic waste
- Recycled material in the packaging: 30 %

INDUSTRIES

- Automotive/mechanical industry
- Mechanical industry
- Other industries
- Glass industry

APPLICATIONS

- Handling glass sheets
- Handling and sorting small, sharp parts
- Handling oily mechanical parts
- Handling sheet metal
- Machining parts using cutting oil
- Cutting and stamping metal
- Maintenance in wet environments (water, oil, greases, hydrocarbons)
- Maintenance in wet environments





KRYTECH 580

Low risk - ISO B


LEGENDS

EN388

MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)




EN407

THERMAL RISKS (HEAT AND FIRE)



PERFORMANCE LEVELS (X = NOT TESTED)





PROTECTION FROM PESTICIDES

GR: Re-entry tasks

ISO 18889

PRODUCT DETAILS

Interior finish	Seamless textile support from HDPE fibres
Gauge	13
Exterior finish	Ventilated back
Material	Nitrile GRIP&PROOF coating
Cuff characteristic	Knitted Cuff
Colour.s	Black Grey
European sizes	6 7 8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	1.3E+10 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	2.1Ε+11 Ω

LOGISTIC DETAILS

Packaging	1 pair/bag 12 pairs/bag
	48 pairs/carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/01/19/0175 updated 03-08/12/2023
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 Asqual 14 rue des Reculettes -75013 Paris -France

(1) Measurement based on life cycle analysis, carried out by Glimpact, an independent third party, according to the European PEF method adopted by European Commission, based a pair of Grip&Proof cut B nitrile gloves.



