

# **KRYTECH 582**

High risk - ISO D

## Special Grip&Proof nitrile coating provides better liquidproofness and grip in oily situations

## SPECIFIC ADVANTAGES



### **Cut protection**

Optimal cut resistance



### Durability

Excellent abrasion resistance increases glove lifetime



### **Productivity**

• Grip and Proof coating ensures an excellent grip in oily environment. It also reduces muscle strain and boost productivity



### Skin protection

• Free of harmful substances: DMF Free



### **Guaranteed quality**

• Silicone free to prevent traces, defects on metal sheet and glass prior to painting



### Washability

• Washable up to 5 times at 60°C, allowing to extend glove lifespan, reduce costs and waste.



### Practical

• Cut level easy to identify thanks to the marking on the back of the glove.



## © Care for the environment

- Optimised individual packaging to limit plastic waste
- Recycled material in the packaging: 30 %





### **CATEGORY 2**

CUT PROTECTION

**LEVEL D** 

**GRIP & PROOF** 

**TECHNOLOGY** 



ISO 13997:

18 N

### DEXTERITY

EN420: 5/5



## **INDUSTRIES**

- Automotive/mechanical industry
- Mechanical industry
- Glass industry

### **APPLICATIONS**

- Handling glass sheets
- Assembly of thin metal sheets
- Finishing sharp parts
- Handling metal parts
- Metal rolling, stamping and assembly
- Metal working
- Cutting and stamping metal






# KRYTECH 582

High risk - ISO D

# ( LEGENDS )



## PRODUCT DETAILS

| Interior finish   | Seamless textile support from HDPE fibres |
|---|---|
| Gauge   | 13  |
| Exterior finish   | Non-slip grip                             |
| Material  | Nitrile GRIP&PROOF coating                |
| Cuff characteristic   | Knitted Cuff                              |
| Colour.s  | Black Blue                                |
| European sizes  | 6 7 8 9 10 11                             |
| Surface resistance according<br>to EN1149-1 (Value in palm<br>area at 25% relative humidity)  | 5.9E+9 Ω                                  |
| Vertical resistance according<br>to EN1149-2 (Value in palm<br>area at 25% relative humidity) | 4.8E+10 Ω                                 |

# LOGISTIC DETAILS

| Packaging | 1 pair/bag<br>12 pairs/bag<br>48 pairs/carton |
|-----------|---|
|-----------|---|

## **LEGISLATION**

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation  $n^{\circ}$  1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/12/18/2873
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE

