



Chemical protection

# ULTRANITRIL 493

Prolonged contact (or immersion) | intermittent wear



KEMIALLINEN SUOJAUS  
TYYPPI A

EN388



4102X

EN ISO 374-1



TYYPPI A  
AJKOPT

EN ISO 374-5



CAT.CATEGORY 3

DEXTERITY



G2  
ISO 18889



0334

EN 420:  
5/5

## Ultra-long chemical protection

### ERITYISIÄ ETUJA



#### Durability

- Longer service life: excellent mechanical resistance (abrasion, perforation)



#### Productivity

- Good grip on slippery objects, due to the embossed texture



#### Skin protection

- Excellent protection during intensive handling of high-risk chemical products



#### Guaranteed quality

- In compliance with guideline for requirements concerning personal protective equipment in plant protection according to BVL (Bundesamt für Verbraucherschutz und Lebensmittelsicherheit)
- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

### TEOLLISUUDELLE

- Automotive/mechanical industry
- Chemical industry
- Other industries
- Agriculture sector

### SOVELLUKSET

- Spray mixtures preparation
- Pesticides handling
- Tank filling
- Application & spreading of pesticides
- Pesticides waste management
- Treatment equipment cleaning
- Handling drums of chemical products
- Application of pesticides
- Cleaning of printing-press rollers
- Maintenance

Muokata 30/06/2023

MAPA SAS capital de 35.000.010 €  
420, rue d'Estienne d'Orves  
92705 Colombes Cedex France  
RCS Nanterre 314 307 720

mapa-pro.com

**MAPA**  
PROFESSIONAL



Chemical protection

# ULTRANITRIL 493

Prolonged contact (or immersion) | intermittent wear

## LEGENDOJA

<b>EN388</b>	<b>MECHANICAL HAZARDS</b>
	<b>PERFORMANCE LEVELS (X = NOT TESTED)</b>
<b>4 1 0 2 X</b>	
0-4 0-5 0-4 0-4 A-F P	
	Impact protection (optional)
	Cut resistance according to ISO 13997
	Puncture resistance
	Tear resistance
	Blade cut resistance
	Abrasion resistance
<b>EN ISO 374-1</b>	<b>CHEMICAL RISKS</b>
	A: Methanol
<b>TYYPPI A</b>	J: n-Heptane
	K: Sodium hydroxide 40%
	O: Ammonia 25%
	P: Hydrogen peroxide 30%
	T: Formaldehyde 37%
	<b>PROTECTION FROM PESTICIDES</b>
<b>G2</b>	G2: Diluted & concentrated pesticides / Mechanical risk
<b>ISO 18889</b>	
<b>EN ISO 374-5</b>	<b>MICRO-ORGANISMS</b>
	Protection against bacteria and fungi

## TUOTTEEN YKSITYISKOHDAT

Interior finish	Flocked
Exterior finish	Embossed texture
Material	Nitrile
Cuff characteristic	Straight cuff
Colour.s	Green
Length (cm)	39
Thickness (mm)	0.55
European sizes	8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	8.3E+10 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	1.2E+10 Ω

## LOGISTISET YKSITYISKOHDAT

Packaging	12 pairs/bag 48 pairs/carton
-----------	---------------------------------

## LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/12/15/1212
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France

Muokata 30/06/2023