

KRYTECH 576

High-performance protection for intricate handling in reasonably clean environments



VIILTOSUOJA
TASO D

EN388



4X42D

CAT.CATEGORY 2



DEXTERITY

EN 420:
5/5

ERITYISIÄ ETUJA



Cut protection

- Optimal cut resistance: level 5 (ANSI Cut 4)



Comfort

- Excellent dexterity due to the precise fit
- Added comfort and flexibility



Skin protection

- Contains traces of DMF in compliance with occupational exposure limits


TEOLLISUUELLE

- Automotive/mechanical industry
- Local Authorities (Technical Maintenance)
- Construction Industry (Roofers/Tilers/Glazers)
- Plastics industry

SOVELLUKSET

- Post-injection material removal
- Maintenance work with risk of cuts
- Handling and fitting windows
- Assembly of thin metal sheets
- Finishing sharp parts
- Handling metal parts

LEGENDOJA

EN388	MECHANICAL HAZARDS
	PERFORMANCE LEVELS (X = NOT TESTED)
4 X 4 2 D	
0-4 0-5 0-4 0-4 A-F P	
	Impact protection (optional)
	Cut resistance according to ISO 13997
	Puncture resistance
	Tear resistance
	Blade cut resistance
	Abrasion resistance

TUOTTEEN YKSITYISKOHDAT

Interior finish	Seamless textile support from HDPE fibres
Gauge	13
Exterior finish	Ventilated back
Material	Polyurethane
Cuff characteristic	Knitted Cuff
Colour.s	Grey
Length (cm)	22-27

LOGISTISET YKSITYISKOHDAT

Packaging	1 pair/bag 12 pairs/bag 96 pairs/carton
-----------	---

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain any substances of very high concern according to the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/01/19/0137
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE