



Cut protection

KRYTECH 586

High risk - ISO D

High-performance protection for intricate handling in reasonably clean environments



VIILTOSUOJA
TASO D

EN388



4X43D

CAT.CATEGORY 2



DEXTERITY

EN 420:
5/5

ISO 13997:

18.6 N

ERITYISIÄ ETUJA



Cut protection

- Optimal cut resistance



Comfort

- Excellent dexterity due to the precise fit
- Added comfort and flexibility



Skin protection

- Contains traces of DMF in compliance with occupational exposure limits



Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting



Washability

- Washable up to 3 times at 60°C without any alteration on performances* allowing to extend glove lifespan, reduce costs and waste.



Practical

- A visible indicator in blue textile to easily identify the cut-performance level in the workplace Washable until 3 cleaning cycles (see laundering and drying conditions)

TEOLLISUUELLE

- Automotive/mechanical industry
- Local Authorities (Technical Maintenance)
- Construction Industry (Roofers/Tilers/Glazers)
- Plastics industry

SOVELLUKSET

- Post-injection material removal
- Maintenance work with risk of cuts
- Handling and fitting windows
- Assembly of thin metal sheets
- Finishing sharp parts
- Handling metal parts

Muokata 30/06/2023

MAPA SAS capital de 35.000.010 €
420, rue d'Estienne d'Orves
92705 Colombes Cedex France
RCS Nanterre 314 307 720

mapa-pro.com

MAPA
PROFESSIONAL



Cut protection

KRYTECH 586

High risk - ISO D

LEGENDOJA

EN388		MECHANICAL HAZARDS	
PERFORMANCE LEVELS (X = NOT TESTED)			
4	X	4	3 D
0-4	0-5	0-4	0-4 A-F P
Impact protection (optional)			
Cut resistance according to ISO 13997			
Puncture resistance			
Tear resistance			
Blade cut resistance			
Abrasion resistance			

TUOTTEEN YKSITYISKOHDAT

Interior finish	Seamless textile support from HDPE fibres
Gauge	13
Exterior finish	Ventilated back
Material	Polyurethane
Cuff characteristic	Knitted Cuff
Colour.s	Grey Blue
European sizes	6 7 8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	1.3E+11 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	1.5E+10 Ω

LOGISTISET YKSITYISKOHDAT

Packaging	1 pair/bag 12 pairs/bag 48 pairs/carton
-----------	---

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/01/19/0209
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE

* Testit on suoritettu käyttämättömillä käsineillä (ts. uusilla käsineillä), jotka poikkeavat todellisista käyttöolosuhteista.

Muokata 30/06/2023

MAPA SAS capital de 35.000.010 €
420, rue d'Estienne d'Orves
92705 Colombes Cedex France
RCS Nanterre 314 307 720

mapa-pro.com

MAPA
PROFESSIONAL