# **TEMPICE 700**

Temperature to -10°C | Wet environments

#### Reinforced Durability to push the limits of cold





EN388



EN 511:2006 (COLD)



02X

DEXTERITY

EN 420: 5/5

## **SPESIFIKKE FORDELER**

#### Comfort

Stay dry when working in wet conditions



#### Durability

Coating 5 times as durable than standard gloves on the market



#### **Productivity**

- Excellent grip when handling wet parts
- Grip and Proof coating ensures an excellent grip in very oily environment . It also reduces muscle strain and boosts productivity



**Guaranteed quality** 

• Silicone free to prevent traces, defects on metal sheet and glass prior to painting



**CAT.CATEGORY 2** 

#### Washability

 Washable up to 5 times at 60°C without any alteration on performances\* allowing to extend glove lifespan, reduce costs and waste.

### **NÆRINGER**

- Local Authorities (Catering) Services)
- Local Authorities (Roads and Highways)
- Local Authorities (Parks and Public Spaces)
- Local Authorities (Waste Collection and Processing)
- Other industries
- Transport, logistics

### **APPLIKASJONER**

- Order preparation
- Maintaining the roads
- Waste collection
- Public park maintenance
- Construction materials handling
- Maintenance in wet or cold environments

Redigere 30/06/2023



# **TEMPICE 700**

Temperature to -10°C | Wet environments

# **LEGENDER**

EN388

MECHANICAL HAZARDS

PERFORMANCE LEVELS (X = NOT

Impact protection (optional) Cut resistance according to ISO 13997 Puncture resistance Tear resistance Blade cut resistance

EN 511:2006 (Cold)

**COLD HAZARDS** 



Redigere 30/06/2023

PERFORMANCE LEVELS (X = NOT TESTED)

Abrasion resistance

Water permeability Contact cold resistance Convective cold resistance

## PRODUKT DETALJER

Interior finish	Knitted thermal protection
Gauge	10
Exterior finish	Non-slip grip
Material	Nitrile GRIP&PROOF coating
Cuff characteristic	Knitted Cuff
Colour.s	Black Blue
European sizes	7 8 9 10
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	7.6Ε+9 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	3.5E+11 Ω

# LOGISTISKE DETALJER

Packaging	1 pair/bag 12 pairs/bag
	72 pairs/carton

## **LEGISLATION**

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation no 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/08/18/1671
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE

\* Tester ble utført på ubrukte hansker (dvs. nye), dette avviker fra realiteten ute i felt.

