



Chemical protection

FLUOTECH 468

short wear

Tactile sensitivity with wear-indicator



KJEMISK BESKYTTELSE
TYPE A



3102X

EN ISO 374-1



TYPE A
ADEFGJLMNO

EN ISO 374-5



CAT.CATEGORY 3

DEXTERITY

EN 420:
5/5



0334

SPESIFIKKE FORDELER



Comfort

- Excellent flexibility and thickness optimization, due to the Mapa multi-layer technology: good dexterity and comfort



Durability

- Nitrile inner layer: excellent mechanical resistance and a longer service life



Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting



Practical

- Green inner layer: wear-indicator for greater user safety

NÆRINGER

- Mechanical industry
- Chemical industry
- Other industries

APPLIKASJONER

- Metal degreasing and etching
- Chemical treatments (solvents)
- Galvanoplasty
- Handling and transporting chemicals (solvents)
- Manufacturing paints and varnishes
- Resin and adhesive manufacturing
- Petrochemical refining
- Printing
- Site pollution control



Chemical protection

FLUOTECH 468

short wear

LEGENDER

| | |
|-----------------------|--|
| EN388 | MECHANICAL HAZARDS |
| | |
| 3 1 0 2 X | PERFORMANCE LEVELS (X = NOT TESTED) |
| 0-4 0-5 0-4 0-4 A-F P | |
| | Impact protection (optional) |
| | Cut resistance according to ISO 13997 |
| | Puncture resistance |
| | Tear resistance |
| | Blade cut resistance |
| | Abrasion resistance |

| | |
|---------------------|--|
| EN ISO 374-1 | CHEMICAL RISKS |
| | |
| TYPE A | A: Methanol D: Dichloromethane E: Carbon Disulfide F: Toluene G: Diethylamine J: n-Heptane L: Sulphuric acid 96% M: Nitric acid 65% N: Acetic acid 99% O: Ammonia 25% |

| | |
|---------------------|---------------------------------------|
| EN ISO 374-5 | MICRO-ORGANISMS |
| | Protection against bacteria and fungi |

PRODUKT DETALJER

| | |
|---------------------|-----------------|
| Interior finish | Chlorinated |
| Exterior finish | Smooth |
| Material | Fluoroelastomer |
| Cuff characteristic | Feston Cuff |
| Colour.s | Black |
| Length (cm) | 30 |
| Thickness (mm) | 0.51 |
| European sizes | 8 9 10 |

LOGISTISKE DETALJER

| | |
|-----------|---------------|
| Packaging | 1 pair/carton |
|-----------|---------------|

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/01/19/0326
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France

Redigere 30/06/2023