# **ULTRANEO 339**

Prolonged contact (or immersion) | continous wear

#### Comfort and high-level chemical protection

# Thermal protection

## SPESIFIKKE FORDELER

• Thermal insulation from the cotton-knit lining for handling hot liquids



• Excellent mechanical resistance and longer service life, due to the textile support and the thickness of the glove



Pebbled embossing, for better grip on wet and slippery objects



• Superior chemical resistance against acids and alkalis, such as concentrated hydrofluoric acid, oils, and greases, due to its 100% neoprene multi-layer construction



• Silicone free to prevent traces, defects on metal sheet and glass prior to painting

#### K JEMISK BESKYTTEI SE **TYPE A**



EN ISO 374-1



TYPE A **ABCJLMNS** 

EN407



X1XXXX

**CATEGORY 3** 



0334

#### **NÆRINGER**

- Mechanical industry
- Chemical industry

# **APPLIKASJONER**

- Surface treatment of metals (acids)
- Handling and transporting drums of chemical products
- Handling on alkylation units
- Hot, petrochemical product sampling
- Resin-working
- Site pollution control

Redigere 04/10/2023

# **ULTRANEO 339**

Prolonged contact (or immersion) | continous wear

# **LEGENDER**

EN388

**MECHANICAL HAZARDS** 

PERFORMANCE LEVELS (X = NOT


Impact protection (optional) Cut resistance according to ISO 13997 Puncture resistance Tear resistance Blade cut resistance Abrasion resistance

EN407

THERMAL RISKS (HEAT AND FIRE)



PERFORMANCE LEVELS (X = NOT



#### EN ISO 374-1

Limited flame spread



**CHEMICAL RISKS** A: Methanol

- B: Acetone
- C: Acetonitrile
- J: n-Heptane
- L: Sulphuric acid 96%
- M: Nitric acid 65%
- N: Acetic acid 99%
- S: Hydrofluoric acid 40%

#### PRODUKT DETALJER

Interior finish	Textile support
Exterior finish	Pebbled
Material	Polychloroprene
Cuff characteristic	Feston Cuff
Colour.s	Black
Length (cm)	36
Thickness (mm)	1.6
European sizes	9 10
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	2.9E+11 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	1.2E+11 Ω

## LOGISTISKE DETALJER

Packaging 1 pair/	′bag
6 pair	s/carton

#### **LEGISLATION**

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation no 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/12/18/2912 updated 01-11/10/2021
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 Asqual 14 rue des Reculettes -75013 Paris -France

