



Handling protection

ULTRANE 500

Grip and skin protection for oily environments.



GRIP & PROOF
TECHNOLOGY



EN388
4121A



EN407
X1XXXX



ISO 18889
GR

CAT.CATEGORY 3

ISO 13997:

DEXTERITY



0075

5 N

EN 420:
5/5



SPESIFIKKE FORDELER



Durability

- Color adapted to dirty environments for a prolonged durability.
- Excellent abrasion resistance due to the nitrile coating



Productivity

- Grip and Proof coating ensures an excellent grip in oily environment. It also reduces muscle strain and boost productivity



Skin protection

- Oilproof, it repels oil penetration and reduce dermatitis
- Free of harmful substances: DMF Free



Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting



Washability

- Washable 3 times at 40° without any alteration on performances* to extend lifespan, reduce costs and waste



Additional benefits

- Available in vending machine packaging

NÆRINGER

- Automotive/mechanical industry
- Mechanical industry
- Other industries
- Glass industry
- Agriculture sector

APPLIKASJONER

- Handling glass sheets
- Re-entry tasks
- Cutting and stamping metal
- Maintenance in wet environments (water, oil, greases, hydrocarbons)
- Maintenance in wet environments
- Handling and sorting small, sharp parts
- Handling oily mechanical parts
- Handling sheet metal
- Machining parts using cutting oil

Redigere 30/06/2023

MAPA SAS capital de 35.000.010 €
420, rue d'Estienne d'Orves
92705 Colombes Cedex France
RCS Nanterre 314 307 720

mapa-pro.com



MAPA
PROFESSIONAL



Handling protection

ULTRANE 500

LEGENDER



PRODUKT DETALJER

| | |
|---|----------------------------|
| Interior finish | Seamless textile support |
| Gauge | 13 |
| Exterior finish | Ventilated back |
| Material | Nitrile GRIP&PROOF coating |
| Cuff characteristic | Knitted Cuff |
| Colour.s | Black |
| European sizes | 6 7 8 9 10 11 |
| Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity) | 1.1E+10 Ω |
| Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity) | 4.4E+11 Ω |

LOGISTISKE DETALJER

| | |
|-----------|---|
| Packaging | 1 pair/bag 12 pairs/bag 96 pairs/carton |
|-----------|---|

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/09/18/1953
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0075 | CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE