

FLUOTECH 344

continous wear

Comfort and flexibility for extended wear

MAPA 3A4 PLUGTICE TUGTICE TU

KJEMISK BESKYTTELSE

TYPE A

EN388



3121X

EN407



EN ISO 374-1

EN ISO 374-5

DEXTERITY EN 420: 2/5



TYPE A ACDEFGJLMN

CAT.CATEGORY 3



0334

SPESIFIKKE FORDELER

Comfort

- Excellent comfort for long tasks, due to the cotton-knit interior
- Freedom of movement: good glove flexibility

Durability

• High mechanical resistance and long service life, due to textile support



• Silicone free to prevent traces, defects on metal sheet and glass prior to painting

NÆRINGER

- Mechanical industry
- Chemical industry
- Other industries

APPLIKASJONER

- Metal degreasing and etching
- Chemical treatments (solvents)
- Galvanoplasty
- Handling and transporting chemicals (solvents)
- Manufacturing paints and varnishes
- Resin and adhesive manufacturing
- Emergency interventions on chemical accidents
- Petrochemical refining
- Printing
- Site pollution control

Redigere 30/06/2023

FLUOTECH 344

continous wear

LEGENDER

EN388

MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)

3 1 2 1 X P P P | Impact protection (optional)

Cut resistance according to ISO 13997

Puncture resistance
Blade cut resistance
Blade cut resistance

EN407

Abrasion resistance

THERMAL RISKS (HEAT AND FIRE)



PERFORMANCE LEVELS (X = NOT TESTED)



Resistance to large quantities of molten metal

Small splashes of molten metal

Radiant heat resistant Convective heat resistance

Contact heat resistance

EN ISO 374-1



CHEMICAL RISKS A: Methanol

- C: Acetonitrile
- D: Dichloromethane
- E: Carbon Disulfide
- F: Toluene
- G: Diethylamine
- J: n-Heptane
- L: Sulphuric acid 96%
- M: Nitric acid 65%
- N: Acetic acid 99%

EN ISO 374-5

MICRO-ORGANISMS



Protection against bacteria and fungi

PRODUKT DETALJER

Interior finish	Textile support
Exterior finish	Smooth
Material	Fluoroelastomer
Cuff characteristic	Feston Cuff
Colour.s	Black
Length (cm)	37
Thickness (mm)	1.6
European sizes	9 10
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	2.7Ε+10 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	4.3E+10 Ω

LOGISTISKE DETALJER

Packaging 1 pair/bag 1 pair/carton	
------------------------------------	--

LEGISLATION

- $\,$ This product is not classified hazardous according to the regulation (EC) $\,$ n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/02/19/0479 updated 01-11/10/2021
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 Asqual 14 rue des Reculettes -75013 Paris -France

Redigere 30/06/2023