

# **KRYTECH 585**

Moderate risk - ISO C

# Enhanced safety, comfort and durability with Grip & Proof Technology

#### SPESIFIKKE FORDELER



#### **Cut protection**

Optimal cut resistance



#### Comfort

 A seamless plaited glove and an optimized coating covering for a maximum comfort, dexterity and flexibility.



#### Durability

Optimal durability that offers better productivity and optimizes your costs



#### Productivity

Grip and Proof coating ensures an excellent grip in very oily environment.
 It also reduces muscle strain and boosts productivity



#### Washability

 Washable up to 3 times at 60°C without any alteration on performances\* allowing to extend glove lifespan, reduce costs and waste.



#### Practical

• Cut level easy to identify thanks to the marking on the back of the glove.



EN388

4X42C

**GRIP & PROOF** 

**TECHNOLOGY** 

KUTTEBESKYTTELSE NIVÅ C

CAT.CATEGORY 2

ISO 13997:



13 N

DEXTERITY

EN 420: 5/5



#### **NÆRINGER**

- Automotive/mechanical industry
- Food industry
- Construction Industry (Metalworkers/Locksmiths)
- Other industries
- Plastics industry
- Manufacturing

#### **APPLIKASJONER**

- Post-injection material removal
- Handling heavy parts with cut risk
- Cutting & stamping heavy metal sheets
- Maintenance and work in cold stores
- Handling and installing metal structures
- Maintenance in wet or cold environments
- Road works in cold conditions
- Finishing sharp parts
- Handling metal parts
- Handling parts post-press

Redigere 30/06/2023



## KRYTECH 585

Moderate risk - ISO C

# LEGENDER

# PERFORMANCE LEVELS (X = NOT TESTED) 4 X 4 2 C O-4 O-5 O-4 O-4 A-F | Impact protection (optional) | Cut resistance according to ISO 13997 | Puncture resistance | Blade cut resistance | Abrasion resistance

### PRODUKT DETALJER

Interior finish	Seamless textile support from HDPE fibres
Gauge	15
Exterior finish	Ventilated back
Material	Nitrile GRIP&PROOF coating
Cuff characteristic	Knitted Cuff
Colour.s	Black Grey
European sizes	7 8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	2.7E+10 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	3.0E+11 Ω

# LOGISTISKE DETALJER

Packaging	1 pair/bag 12 pairs/bag 48 pairs/carton
-----------	---

#### **LEGISLATION**

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/05/18/0907
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE

<sup>\*</sup> Tester ble utført på ubrukte hansker (dvs. nye), dette avviker fra realiteten ute i felt.

