ULTRANITRIL 492

Frequent contact | intermittent wear

Good mechanical resistance and long-lasting chemical protection

SPESIFIKKE FORDELER



Comfort

• Dexterity and comfort, due to the anatomical shape and the quality of the flock-lining



Durability

• Longer service life: excellent mechanical resistance (abrasion, perforation)



Guaranteed quality

• Silicone free to prevent traces, defects on metal sheet and glass prior to painting



Additional benefits

Available in vending machine packaging



K IEMISK BESKYTTEI SE **TYPE A**

EN388



ISO 18889

AJKOPT

EN ISO 374-1



TYPF A

CAT.CATEGORY 3

EN ISO 374-5



VIRUS



0334

DEXTERITY

EN 420: 5/5

NÆRINGER

- Automotive/mechanical industry
- Local Authorities (Cleaning)
- Local Authorities (Parks and Public Spaces)
- Construction Industry (Masons / Plasterers)
- Construction Industry (Carpenters/Joiners)
- Agriculture sector

APPLIKASJONER

- Spray mixtures preparation
- Pesticides handling
- Tank filling
- Application & spreading of pesticides
- Pesticides waste management
- Treatment equipment cleaning
- Handling oils, solvents, detergents
- Preparing coatings, varnishes
- Handling PVC-based glues
- Handling aggressive chemical products

Redigere 30/06/2023



ULTRANITRIL 492

Frequent contact | intermittent wear

LEGENDER

EN388

MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)

TESTE

3 1 0 1 X

Impact protection (optional)

Cut resistance according to ISO 13997

Puncture resistance

Tear resistance Blade cut resistance

Abrasion resistance

EN ISO 374-1



TYPE A

CHEMICAL RISKS

- A: Methanol
- J: n-Heptane
- K: Sodium hydroxide 40%
- O: Ammonia 25%
- P: Hydrogen peroxide 30%
- T: Formaldehyde 37%



PROTECTION FROM PESTICIDES

G2: Diluted & concentrated pesticides / Mechanical risk

ISO 18889

EN ISO 374-5



VIRUS

MICRO-ORGANISMS

Protection against bacteria, fungi and virus

PRODUKT DETALJER

Interior finish	Flocked
Exterior finish	Embossed texture
Material	Nitrile
Cuff characteristic	Straight cuff
Colour.s	Green
Length (cm)	32
Thickness (mm)	0.38
European sizes	6 7 8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	6.4E+10 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	5.8E+9 Ω

LOGISTISKE DETALJER

1 pair/bag 10 pairs/bag 100 pairs/carton
100 pairs/carton

LEGISLATION

- $\,$ This product is not classified hazardous according to the regulation (EC) $\,$ n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/08/18/1631
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 Asqual 14 rue des Reculettes -75013 Paris -France

