



Cut protection

KRYTECH 615

High risk - ISO D

High cut protection without any compromise on comfort and dexterity. Usable with touch screens.



KUTTEBESKYTTELSE
NIVÅ D

EN388



4X43D

CAT.CATEGORY 2



ISO 13997:

20 N



SPESIFIKKE FORDELER



Cut protection

- High cut protection without any compromise on comfort, dexterity and breathability. Usable with touch screens.



Comfort

- A seamless plaited glove for very good fit, dexterity and flexibility.



Durability

- Optimal durability that offers better productivity and optimizes your costs



Suitable for touchscreen

- Can be used with touch devices & touch screen (thumb & index)



Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting



Washability

- Washable up to 3 times at 60°C without any alteration on performances* allowing to extend glove lifespan, reduce costs and waste.



Practical

- Cut level easy to identify thanks to the marking on the back of the glove.

NÆRINGER

- Automotive/mechanical industry
- Construction Industry (Carpenters/Joiners)
- Construction Industry (Metalworkers/Locksmiths)
- Glass industry
- Industrial equipment / Metal transformation
- Industrial maintenance

APPLIKASJONER

- Handling glass sheets
- Maintenance with cut risk
- Handling of thick metal sheets
- Installing steel structures
- Handling and installing metal structures
- Mechanical maintenance
- Assembly of thin metal sheets
- Cutting aluminium strips
- Handling sheet metal
- Metal working

Redigere 30/06/2023

MAPA SAS capital de 35.000.010 €
420, rue d'Estienne d'Orves
92705 Colombes Cedex France
RCS Nanterre 314 307 720

mapa-pro.com

MAPA
PROFESSIONAL



Cut protection

KRYTECH 615

High risk - ISO D

LEGENDER

EN388		MECHANICAL HAZARDS	
PERFORMANCE LEVELS (X = NOT TESTED)			
4	X	4	3 D
0-4	0-5	0-4	0-4 A-F P
			Impact protection (optional)
			Cut resistance according to ISO 13997
			Puncture resistance
			Tear resistance
			Blade cut resistance
			Abrasion resistance

PRODUKT DETALJER

Interior finish	Seamless textile support from HDPE fibres
Gauge	13
Exterior finish	Ventilated back
Material	Polyurethane
Cuff characteristic	Knitted Cuff
Colour.s	Black Grey
European sizes	6 7 8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	1.0E+10 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	2.9E+9 Ω

LOGISTISKE DETALJER

Packaging	1 pair/bag 12 pairs/bag 48 pairs/carton
-----------	---

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/04/18/0697
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE