



Chemical protection

BUTOFLEX 650

ultra-comfort wear

Ultimate specific chemical resistance



KJEMISK BESKYTTELSE
TYPE A



1121X

EN ISO 374-1



TYPE A
ABCILMNOS

EN ISO 374-5



CAT.CATEGORY 3



0334

DEXTERITY

EN 420:
5/5

SPESIFIKKE FORDELER



Comfort

- Exceptional comfort; the first butyl glove on the market with a fabric inner lining
- Unrivalled flexibility and dexterity



Skin protection

- Ultimate specific chemical resistance, for very corrosive acids, ketones, esters and amine derivatives



Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

NÆRINGER

- Mechanical industry
- Chemical industry
- Cosmetics and Pharmaceutical industry

APPLIKASJONER

- Handling in laboratories
- Metal treatment and degreasing
- Formulating paints, varnishes, resins and inks
- Handling and repackaging chemicals
- Sampling chemicals



Chemical protection

BUTOFLEX 650

ultra-comfort wear

LEGENDER

| | |
|-----------------------|--------------------------------------------|
| EN388 | MECHANICAL HAZARDS |
| | PERFORMANCE LEVELS (X = NOT TESTED) |
| 1 1 2 1 X | |
| 0-4 0-5 0-4 0-4 A-F P | |
| | Impact protection (optional) |
| | Cut resistance according to ISO 13997 |
| | Puncture resistance |
| | Tear resistance |
| | Blade cut resistance |
| | Abrasion resistance |
| EN ISO 374-1 | CHEMICAL RISKS |
| | A: Methanol |
| TYPE A | B: Acetone |
| | C: Acetonitrile |
| | I: Ethyl acetate |
| | L: Sulphuric acid 96% |
| | M: Nitric acid 65% |
| | N: Acetic acid 99% |
| | O: Ammonia 25% |
| | S: Hydrofluoric acid 40% |
| EN ISO 374-5 | MICRO-ORGANISMS |
| | Protection against bacteria and fungi |

PRODUKT DETALJER

| | |
|-----------------------------------------------------------------------------------------|---------------------------------|
| Interior finish | Textile support Mapa Technology |
| Exterior finish | Embossed texture |
| Material | Butyl |
| Cuff characteristic | Feston Cuff |
| Colour.s | Black |
| Length (cm) | 35 |
| Thickness (mm) | 1.45 |
| European sizes | 7 8 9 10 |
| Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity) | 2.0E+5 Ω |
| Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity) | 6.7E+8 Ω |

LOGISTISKE DETALJER

| | |
|-----------|------------------------------|
| Packaging | 1 pair/bag 6 pairs/carton |
|-----------|------------------------------|

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/10/18/2133
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France

Redigere 30/06/2023