Handling protection

ULTRANE 548

Optimal dexterity and sensitivity for light protection



EN 388

3121X

Dexterity EN ISO 21420: 5/5

CATEGORY 2

CE

SPECIFIC ADVANTAGES

Comfort

- Thin glove: excellent tactile sensitivity
- Absorption of perspiration ensured by the cellular structure of the polyurethane. In addition, the particularly open texture of the specific lining helps improve hand ventilation
- Excellent dexterity due to the precise fit

Skin protection

- Contains traces of DMF in compliance with occupational exposure limits

Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

Additional benefits

- Available in vending machine packaging

INDUSTRIES

- Automotive industry
- Electronics
- HEALTH CARE: Cosmetic industry
- HEALTH CARE: Pharmaceutical industry

APPLICATIONS

- Fitting small screws and fasteners
- Microprocessor handling
- Sorting small parts
- Assembly of electrical components
- Cosmetics preparation
- Medicine manufacturing

Edit 02/11/2026

Handling protection

ULTRANE 548

LEGENDS

EN388



MECHANICAL HAZARDS

PERFORMANCE LEVELS (X = NOT TESTED)

3	1	2	1	X	
0-4	0-5	0-4	0-4	A-F	P

- P: Impact protection (optional)
- A-F: Cut resistance according to ISO 13997
- 0-4: Puncture resistance
- 0-4: Tear resistance
- 0-5: Blade cut resistance
- 3: Abrasion resistance

LOGISTIC DETAILS

Packaging	1 pair/bag 12 pairs/bag 96 pairs/carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/03/20/0654
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE

Edit 02/11/2026