



Handling protection

# ULTRANE 553

Unbeatable for fingertip precision in dirty environments



EN 388  
  
4121X

Dexterity EN ISO  
21420: 5/5

CATEGORY 2



## SPECIFIC ADVANTAGES



### Comfort

- Excellent tactile sensitivity and freedom of movement, due to the reduced thickness of the glove



### Durability

- Suitable for long-term wear : excellent abrasion resistance
- Nitrile coating resistant to dirt particles



### Skin protection

- Free of harmful substances: DMF Free



### Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting



### Additional benefits

- Available in vending machine packaging



### Care for the environment

- Optimised individual packaging to limit plastic waste
- Recycled material in the packaging: 30 %

## INDUSTRIES

- Construction industry: Painters/Decorators
- Construction industry: Metalworkers/Locksmiths
- Automotive industry
- Metallurgy
- Food industry
- Local Authorities: Local Authorities (Technical Maintenance)

## APPLICATIONS

- Preparing surfaces
- Handling
- Screwing and bolting
- Sorting small parts
- Pump manufacturing
- Minor maintenance Tasks
- Precision assembly
- Packaging
- Small general maintenance jobs



Handling protection

# ULTRANE 553

## LEGENDS

| EN388                                 |     | MECHANICAL HAZARDS                  |           |
|---------------------------------------|-----|-------------------------------------|-----------|
|                                       |     | PERFORMANCE LEVELS (X = NOT TESTED) |           |
| 4                                     | 1   | 2                                   | 1 X       |
| 0-4                                   | 0-5 | 0-4                                 | 0-4 A-F P |
| Impact protection (optional)          |     |                                     |           |
| Cut resistance according to ISO 13997 |     |                                     |           |
| Puncture resistance                   |     |                                     |           |
| Tear resistance                       |     |                                     |           |
| Blade cut resistance                  |     |                                     |           |
| Abrasion resistance                   |     |                                     |           |

## PRODUCT DETAILS

|                                                                                         |                          |
|-----------------------------------------------------------------------------------------|--------------------------|
| Interior finish                                                                         | Seamless textile support |
| Gauge                                                                                   | 13                       |
| Exterior finish                                                                         | Ventilated back          |
| Material                                                                                | Nitrile                  |
| Cuff characteristic                                                                     | Knitted Cuff             |
| Colour                                                                                  | Black, Grey              |
| Length (cm)                                                                             | 22-26                    |
| Sizes                                                                                   | 5 6 7 8 9 10             |
| Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)  | 1.1E+10 Ω                |
| Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity) | 4.1E+10 Ω                |

## LOGISTIC DETAILS

|           |                                                |
|-----------|------------------------------------------------|
| Packaging | 1 pair/bag<br>10 pairs/bag<br>100 pairs/carton |
|-----------|------------------------------------------------|

## LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/08/18/1657 Update 02-11/04/23
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE

Edit 05/09/2026