



Chemical protection

ULTRANITRIL 493

Prolonged contact (or immersion) | intermittent wear

Ultra-long chemical protection



CHEMICAL PROTECTION
TYPE A

EN 388



4102X

EN 374-1



Type A
AJKOPT

EN 374-5



CATEGORY 3



0334

EN ISO 18889



G2

Dexterity EN ISO
21420: 5/5

SPECIFIC ADVANTAGES



Durability

- Longer service life: excellent mechanical resistance (abrasion, perforation)



Productivity

- Good grip on slippery objects, due to the embossed texture



Skin protection

- Excellent protection during intensive handling of high-risk chemical products



Guaranteed quality

- In compliance with guideline for requirements concerning personal protective equipment in plant protection according to BVL (Bundesamt für Verbraucherschutz und Lebensmittelsicherheit - Federal Office of Consumer Protection and Food Safety)
- Silicone free to prevent traces, defects on metal sheet and glass prior to painting



Care for the environment

- Optimised individual packaging to limit plastic waste
- Recycled material in the packaging: 30 %

INDUSTRIES

- Agriculture sector
- Laboratory
- Automotive industry
- Paper industry
- Food industry

APPLICATIONS

- Spray mixtures preparation
- Pesticides handling
- Tank filling
- Application & spreading of pesticides
- Pesticides waste management
- Treatment equipment cleaning
- Handling and transport of chemical products
- Treating/degreasing metals with aggressive solvents
- Printing
- Application of phytosanitary products



Chemical protection

ULTRANITRIL 493

Prolonged contact (or immersion) | intermittent wear

LEGENDS

EN388	MECHANICAL HAZARDS
	PERFORMANCE LEVELS (X = NOT TESTED)
4 1 0 2 X	
0-4 0-5 0-4 0-4 A-F P	
	Impact protection (optional)
	Cut resistance according to ISO 13997
	Puncture resistance
	Tear resistance
	Blade cut resistance
	Abrasion resistance
EN ISO 374-1	CHEMICAL RISKS
	A: Methanol
TYPE A	J: n-Heptane
	K: Sodium hydroxide 40%
	O: Ammonia 25%
	P: Hydrogen peroxide 30%
	T: Formaldehyde 37%
	PROTECTION FROM PESTICIDES
G2	G2: Diluted & concentrated pesticides / Mechanical risk
ISO 18889	
EN ISO 374-5	MICRO-ORGANISMS
	Protection against bacteria and fungi

PRODUCT DETAILS

Interior finish	Flocked
Exterior finish	Embossed texture
Material	Nitrile
Cuff characteristic	Straight cuff
Colour	Green
Length (cm)	39
Thickness (mm)	0.55
Sizes	8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	8.3E+10 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	1.2E+10 Ω

LOGISTIC DETAILS

Packaging	1 pair/bag 12 pairs/bag 48 pairs/carton
-----------	---

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/12/15/1212
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France

Edit 08/09/2026