Handling protection

ULTRANE 541 NO MARKING



RESICOMFORT TECHNOLOGY

EN 388
4121A

EN 407
X1XXXX

ISO 13997
2,5 N (204 g)

Dexterity EN ISO 21420: 5/5

French decree of 05/08/2020

CATEGORY 2

CE

OEKO TEX® STANDARD 100 CQ 979/2 IFTH

SPECIFIC ADVANTAGES

Comfort
- Comfort: high suppleness and flexibility, dexterity at fingertips, proven breathability

Durability
- Resistance: Extended use guaranteed by our exclusive process ResiComfort, coating provides resistance to friction

Skin protection
- Free of harmful substances: OEKO-TEX® STANDARD 100, DMF Free
- Dermatologically approved

Guaranteed quality
- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

Washability
- Washable 1 time at 40°C

INDUSTRIES
- Automotive industry
- Mining industry
- Metallurgy
- Food industry

APPLICATIONS
- Fitting small screws and fasteners
- Mechanical maintenance
- Precision mechanical work
- Assembly of small parts
- Automotive assembly
- Precision assembly
- Food handling
- Packaging

Edit 06/11/2026

Handling protection

ULTRANE 541 NO MARKING

LEGENDS

EN388 — MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)

4	1	2	1	A	
0-4	0-5	0-4	0-4	A-F	P

- P: Impact protection (optional)
- A-F: Cut resistance according to ISO 13997
- 0-4: Puncture resistance
- 0-4: Tear resistance
- 0-5: Blade cut resistance
- 0-4: Abrasion resistance

EN407 — THERMAL RISKS (HEAT AND FIRE)



PERFORMANCE LEVELS (X = NOT TESTED)

X	1	X	X	X	X
0-4	0-4	0-4	0-4	0-4	0-4

- 0-4: Resistance to large quantities of molten metal
- 0-4: Small splashes of molten metal
- 0-4: Radiant heat resistant
- 0-4: Convective heat resistance
- 0-4: Contact heat resistance
- 1: Limited flame spread



FOOD CONTACT
French decree of 05/08/2020

PRODUCT DETAILS

Interior finish	Seamless textile support
Gauge	15
Exterior finish	Reinforced grip
Material	Nitrile foam sandy
Cuff characteristic	Knitted Cuff
Colour	Black
Length (cm)	22-28
Sizes	6 7 8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	2.0E+11 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	2.1E+12 Ω

LOGISTIC DETAILS

Packaging	12 pairs/bag 96 pairs/carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- This product is in compliance with the regulation 1935/2004/EC of the European parliament and the council on materials and articles intended to come into contact with food and the French Decree of 05/08/2020.
- UE type certificate or CE type examination certificate: 0075/014/162/04/19/1047 update 02-16/02/2022
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE

Edit 06/11/2026