Chemical protection

# ULTRANITRIL 495

Flocked | intermittent wear

The solution for safely handling fatty food products




CHEMICAL PROTECTION
**TYPE A**

EN 388
3101X

EN 374-1
Type A
AJKOPT

EN 374-5

Dexterity EN ISO 21420: 5/5

BfR XXI - Germany
French decree of 05/08/2020

CATEGORY 3

CE
0334

## SPECIFIC ADVANTAGES

### Comfort

- Excellent dexterity and comfort thanks to the anatomical form and the flocklined finish

### Productivity

- Good grip due to the embossed texture

### Skin protection

- Worn alone or as an outer-glove Recommended for persons sensitized to natural rubber proteins.

### Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

## INDUSTRIES

- Food industry

## APPLICATIONS

- Food handling
- Filleting Fish
- Cutting meat and fish

Edit 12/11/2026

Chemical protection

# ULTRANITRIL 495

Flocked | intermittent wear

## LEGENDS

EN388

MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)

| 3 | 1 | 0 | 1 | X | |
|---|---|---|---|---|---|
| 0-4 | 0-5 | 0-4 | 0-4 | A-F | P |

- P: Impact protection (optional)
- A-F: Cut resistance according to ISO 13997
- 0-4: Puncture resistance
- 0-4: Tear resistance
- 0-5: Blade cut resistance
- 3: Abrasion resistance

EN ISO 374-1

CHEMICAL RISKS



TYPE A

A: Methanol
J: n-Heptane
K: Sodium hydroxide 40%
O: Ammonia 25%
P: Hydrogen peroxide 30%
T: Formaldehyde 37%

EN ISO 374-5

MICRO-ORGANISMS



Protection against bacteria and fungi



FOOD CONTACT

French decree of 05/08/2020
BfR XXI - Germany

## PRODUCT DETAILS

| | |
|---|---|
| Interior finish | Flocked |
| Exterior finish | Embossed texture |
| Material | Nitrile |
| Colour | Blue |
| Length (cm) | 32 |
| Thickness (mm) | 0.41 |
| Sizes | 5 6 7 8 9 10 |
| Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity) | 5.1E+10 Ω |
| Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity) | 7.9E+8 Ω |
| **Life Cycle Analysis (kg CO2eq) | 1.18 |

**Calculated according to the European PEF methodology (EF 3.1), in accordance with ISO 14040 and ISO 14044. Cradle-to-grave scope, excluding the use phase. LCA data extracted in September 2026. Calculated on the standard reference.

## LOGISTIC DETAILS

| | |
|---|---|
| Packaging | 1 pair/bag<br>10 pairs/bag<br>100 pairs/carton |

## LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- This product is in compliance with the regulation 1935/2004/EC of the European parliament and the council on materials and articles intended to come into contact with food the French Decree of 05/08/2020, and the German recommendation BfR XXI.
- UE type certificate or CE type examination certificate: 0075/014/162/08/18/1648
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France

Edit 12/11/2026