Chemical protection

ULTRANEO 339

Prolonged contact (or immersion) | continous wear

Comfort and high-level chemical protection



CHEMICAL PROTECTION
TYPE A

EN 388
3121X

EN 374-1
Type A
ABCJLMNS

EN 407
X1XXXX

CATEGORY 3

Dexterity EN ISO 21420: 5/5

CE
0334

SPECIFIC ADVANTAGES

Thermal protection

- Thermal insulation from the cotton-knit lining for handling hot liquids

Durability

- Excellent mechanical resistance and longer service life, due to the textile support and the thickness of the glove

Productivity

- Pebbled embossing, for better grip on wet and slippery objects

Skin protection

- Superior chemical resistance against acids and alkalis, such as concentrated hydrofluoric acid, oils, and greases, due to its 100% neoprene multi-layer construction

Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

INDUSTRIES

- Petroleum and gas industry
- Chemical industry
- Laboratory
- Metallurgy

APPLICATIONS

- Sampling of hot petrochemical products
- Resin-working
- Handling on alkylation units
- Site pollution control
- Handling and transport of chemical products
- Surface treatment of metals (acids)

Edit 10/11/2026

Chemical protection

ULTRANEO 339

Prolonged contact (or immersion) | continous wear

LEGENDS

EN388 — MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)

3	1	2	1	X	
0-4	0-5	0-4	0-4	A-F	P

- P: Impact protection (optional)
- A-F: Cut resistance according to ISO 13997
- 0-4: Puncture resistance
- 0-4: Tear resistance
- 0-5: Blade cut resistance
- 0-4: Abrasion resistance

EN407 — THERMAL RISKS (HEAT AND FIRE)



PERFORMANCE LEVELS (X = NOT TESTED)

X	1	X	X	X	X
0-4	0-4	0-4	0-4	0-4	0-4

- 0-4: Resistance to large quantities of molten metal
- 0-4: Small splashes of molten metal
- 0-4: Radiant heat resistant
- 0-4: Convective heat resistance
- 0-4: Contact heat resistance
- 1: Limited flame spread

EN ISO 374-1 — CHEMICAL RISKS



TYPE A

A: Methanol
B: Acetone
C: Acetonitrile
J: n-Heptane
L: Sulphuric acid 96%
M: Nitric acid 65%
N: Acetic acid 99%
S: Hydrofluoric acid 40%

PRODUCT DETAILS

Interior finish	Textile support
Exterior finish	Pebbled
Material	Polychloroprene
Cuff characteristic	Feston Cuff
Colour	Black
Length (cm)	36
Thickness (mm)	1.35
Sizes	9 10
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	2.9E+11 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	1.2E+11 Ω

LOGISTIC DETAILS

Packaging	1 pair/bag 6 pairs/carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/12/18/2912
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France

Edit 10/11/2026