



Cut protection

KRYTECH 585

Moderate risk - ISO C

Enhanced safety, comfort and durability with Grip & Proof Technology

SPECIFIC ADVANTAGES



Cut protection

- Optimal cut resistance



Comfort

- A seamless plaited glove and an optimized coating covering for a maximum comfort, dexterity and flexibility.



Durability

- Optimal durability that offers better productivity and optimizes your costs



Productivity

- Grip and Proof coating ensures an excellent grip in very oily environment . It also reduces muscle strain and boosts productivity



Skin protection

- Free of harmful substances: DMF Free



Washability

- Washable up to 3 times at 60°C , allowing to extend glove lifespan, reduce costs and waste.



Practical

- Cut level easy to identify thanks to the marking on the back of the glove.



GRIP & PROOF
TECHNOLOGY

CUT PROTECTION
LEVEL C

EN 388



4X42C

ISO 13997
13 N (1325 g)

Dexterity EN ISO
21420: 5/5

CATEGORY 2



STANDARD
100

CQ 979/2
IFTH

INDUSTRIES

- Automotive industry
- Construction industry: Metalworkers/Locksmiths
- Plastics industry
- Mining industry
- Metallurgy
- Food industry
- Local Authorities: Local Authorities (Roads and Highways)

APPLICATIONS

- Finishing sharp parts
- Handling metal parts
- Handling parts post-press
- Handling
- Post-injection material removal
- Handling heavy parts with cut risk
- Cutting & stamping heavy metal sheets
- Machining parts using cutting oil
- Maintenance in wet environments (water, oil, greases, hydrocarbons)
- Maintenance and work in cold stores



Cut protection

KRYTECH 585

Moderate risk - ISO C

LEGENDS

EN388		MECHANICAL HAZARDS	
		PERFORMANCE LEVELS (X = NOT TESTED)	
4	X	4	2 C
0-4	0-5	0-4	0-4 A-F P
		Impact protection (optional)	
		Cut resistance according to ISO 13997	
		Puncture resistance	
		Tear resistance	
		Blade cut resistance	
		Abrasion resistance	

PRODUCT DETAILS

Interior finish	Seamless textile support from HDPE fibres
Gauge	15
Exterior finish	Ventilated back
Material	Nitrile GRIP&PROOF coating
Cuff characteristic	Knitted Cuff
Colour	Black, Grey
Length (cm)	23-27
Sizes	7 8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	2.7E+10 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	3.0E+11 Ω

LOGISTIC DETAILS

Packaging	1 pair/bag 12 pairs/bag 48 pairs/carton
-----------	---

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/05/18/0907
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE

Edit 03/09/2026