Chemical protection

ALTO 415

Frequent contact | intermittent wear

Fine touch for light chemical protection



CHEMICAL PROTECTION
TYPE B

EN 388
1011X

EN 374-1
Type B
KMT

EN 374-5

EN 421

Dexterity EN ISO
21420: 5/5

CATEGORY 3
CE
0334

SPECIFIC ADVANTAGES

Comfort

- Tactile sensitivity, due to the gloves reduced thickness
- Added comfort and absorption of perspiration, due to the cotton flock-lining

Productivity

- Good grip, due to the non-slip embossing

Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

Care for the environment

- Optimised individual packaging to limit plastic waste
- Recycled material in the packaging: 30 %

INDUSTRIES

- Transports
- Automotive industry
- Local Authorities: Cleaning

APPLICATIONS

- Work with composite materials (resins)
- Spray-painting
- Common cleaning Tasks

Edit 16/11/2026

Chemical protection

ALTO 415

Frequent contact | intermittent wear

LEGENDS

EN388

MECHANICAL HAZARDS

PERFORMANCE LEVELS (X = NOT TESTED)

1	0	1	1	X	
0-4	0-5	0-4	0-4	A-F	P

- P: Impact protection (optional)
- A-F: Cut resistance according to ISO 13997
- 0-4: Puncture resistance
- 0-4: Tear resistance
- 0-5: Blade cut resistance
- 1: Abrasion resistance

EN ISO 374-1

CHEMICAL RISKS

K: Sodium hydroxide 40%
M: Nitric acid 65%
T: Formaldehyde 37%

TYPE B

EN 421

RADIOACTIVE CONTAMINATION

EN ISO 374-5

MICRO-ORGANISMS

Protection against bacteria and fungi

PRODUCT DETAILS

Interior finish	Flocked
Exterior finish	Embossed texture
Material	Polychloroprene and natural latex
Cuff characteristic	Straight cuff
Colour	Black
Length (cm)	32
Thickness (mm)	0.6
Sizes	6 7 8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	6.5E+12 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	6.6E+12 Ω
**Life Cycle Analysis (kg CO2eq)	0.61

**Calculated according to the European PEF methodology (EF 3.1), in accordance with ISO 14040 and ISO 14044. Cradle-to-grave scope, excluding the use phase. LCA data extracted in September 2026. Calculated on the standard reference.

LOGISTIC DETAILS

Packaging	1 pair/bag 10 pairs/bag 100 pairs/carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/08/18/1643
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France

Edit 16/11/2026