Cut protection

KRYTECH 693

Moderate risk - ISO C



CUT PROTECTION
LEVEL C

EN 388
4X42C

EN 16350

ISO 13997
14.5 N (1478 g)

Dexterity EN ISO 21420: 5/5

French decree of 05/08/2020

CATEGORY 2

CE

Comfort, suppleness and high dexterity thanks to its 18 gauge. Protection of electronic device from ElectroStatic Discharge (ESD), cut level C and suitable for food contact.

SPECIFIC ADVANTAGES

Cut protection

- Cut level easy to identify thanks to the marking on the back of the glove

Protection of electronic device from ElectroStatic Discharge (ESD)

- Product specifically developed to dissipate electrostatic charges, to protect electronic device from ElectroStatic Discharge (ESD) in compliance with EN16350 (ATEX glove standard)

Durability

- Glove lifetime extended and reinforced security thanks to the crotch reinforcement between thumb and index that protects the glove from any early damage in this very exposed area

Suitable for touchscreen

- Can be used with touch devices & touch screen

Guaranteed quality

- Silicone free to prevent traces or defects prior to painting
- Silicone free to prevent traces, defects on metal sheet and glass

Washability

- Washable 1 time at 40°C

Additional benefits

- 18-gauge for better dexterity

INDUSTRIES

- Automotive industry
- Construction industry: Carpenters/Joiners
- Construction industry: Roofers/Tilers/Glazers
- Construction industry: Heating engineers/Plumbers
- Logistics
- Metallurgy
- Food industry

APPLICATIONS

- Handling metal parts
- Mechanical maintenance
- Precision mechanical work
- Installing steel structures
- Laying tiles, inserts, frames or zinc sheeting
- Operating handling equipment
- Order preparation
- Assembly of small parts
- Automotive assembly
- Assembly of small, oil and grease free parts

Edit 02/11/2026

Cut protection

KRYTECH 693

Moderate risk - ISO C

LEGENDS

EN388

MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)

4	X	4	2	C	
0-4	0-5	0-4	0-4	A-F	P

- P: Impact protection (optional)
- A-F: Cut resistance according to ISO 13997
- 0-4: Puncture resistance
- 0-4: Tear resistance
- 0-5: Blade cut resistance
- 4: Abrasion resistance

EN 16350

PROTECTION AGAINST STATIC ELECTRICITY





FOOD CONTACT

French decree of 05/08/2020

LOGISTIC DETAILS

Packaging	1 pair/bag 12 pairs/bag 48 pairs/carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- This product is in compliance with the regulation 1935/2004/EC of the European parliament and the council on materials and articles intended to come into contact with food and the French Decree of 05/08/2020.
- UE type certificate or CE type examination certificate: 0075/014/162/03/24/0573
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE

Edit 02/11/2026