Chemical protection

# JERSETTE 308

Textile support | continous wear

Good comfort for long-term work for food handling




CHEMICAL PROTECTION
**TYPE B**

EN 388
2131X

EN 374-1
Type B
KPT

EN 407
X1XXXX

Dexterity EN ISO 21420: 5/5

French decree of 05/08/2020

CATEGORY 3
CE
0334

## SPECIFIC ADVANTAGES

### Comfort

- Freedom of movement: anatomical shape and excellent comfort of the textile support (seamless liner on the working surface)
- Waterproof for all uses in wet conditions.

### Durability

- Good tear-resistance

### Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

## INDUSTRIES

- Maritime industry
- Food industry

## APPLICATIONS

- Oyster farming
- Handling frozen products
- Handling fruits and vegetables
- Preparation and packaging

Edit 06/11/2026

Chemical protection

# JERSETTE 308

Textile support | continous wear

## LEGENDS

EN388 — MECHANICAL HAZARDS

PERFORMANCE LEVELS (X = NOT TESTED)

| 2 | 1 | 3 | 1 | X | |
|---|---|---|---|---|---|
| 0-4 | 0-5 | 0-4 | 0-4 | A-F | P |

- P: Impact protection (optional)
- A-F: Cut resistance according to ISO 13997
- 0-4: Puncture resistance
- 0-4: Tear resistance
- 0-5: Blade cut resistance
- 0-4: Abrasion resistance

EN407 — THERMAL RISKS (HEAT AND FIRE)

PERFORMANCE LEVELS (X = NOT TESTED)

| X | 1 | X | X | X | X |
|---|---|---|---|---|---|
| 0-4 | 0-4 | 0-4 | 0-4 | 0-4 | 0-4 |

- 0-4: Resistance to large quantities of molten metal
- 0-4: Small splashes of molten metal
- 0-4: Radiant heat resistant
- 0-4: Convective heat resistance
- 0-4: Contact heat resistance
- 1: Limited flame spread

EN ISO 374-1 — TYPE B

CHEMICAL RISKS
K: Sodium hydroxide 40%
P: Hydrogen peroxide 30%
T: Formaldehyde 37%

FOOD CONTACT
French decree of 05/08/2020

## PRODUCT DETAILS

| | |
|---|---|
| Interior finish | Textile support |
| Exterior finish | Smooth |
| Material | Natural latex |
| Cuff characteristic | Feston Cuff |
| Colour | Blue |
| Length (cm) | 30-32 |
| Thickness (mm) | 1.15 |
| Sizes | 6 7 8 9 10 |
| **Life Cycle Analysis (kg CO2eq) | 7.82 |

**Calculated according to the European PEF methodology (EF 3.1), in accordance with ISO 14040 and ISO 14044. Cradle-to-grave scope, excluding the use phase. LCA data extracted in September 2026. Calculated on the standard reference.

## LOGISTIC DETAILS

| | |
|---|---|
| Packaging | 1 pair/bag<br>5 pairs/bag<br>50 pairs/carton |

## LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- This product is in compliance with the regulation 1935/2004/EC of the European parliament and the council on materials and articles intended to come into contact with food and the French Decree of 05/08/2020.
- UE type certificate or CE type examination certificate: 0075/014/162/05/22/0905 EXT 02/05/22
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France

Edit 06/11/2026