



Chemical protection

ULTRANITRIL 381

Frequent contact | ultra-comfort wear

Maximum comfort and chemical protection



CHEMICAL PROTECTION
TYPE A



Dexterity EN ISO
21420: 5/5

CATEGORY 3



SPECIFIC ADVANTAGES



Thermal protection

- Hand comfort and thermal insulation.



Comfort

- Extremely supple, due to the unique Mapa multi-layer process



Productivity

- Good grip on slippery objects, due to the embossed texture



Additional benefits

- Available in vending machine packaging



Care for the environment

- Plastic packaging optimized, Recycled packaging
- Recycled material in the packaging: 30 %

INDUSTRIES

- Agriculture sector
- Logistics
- Chemical industry
- Laboratory
- Automotive industry
- Metallurgy

APPLICATIONS

- Spray mixtures preparation
- Pesticides handling
- Tank filling
- Application & spreading of pesticides
- Pesticides waste management
- Treatment equipment cleaning
- Maintenance
- Manipulating valves
- Chemical product blending
- Handling and transport of chemical products



Chemical protection

ULTRANITRIL 381

Frequent contact | ultra-comfort wear

LEGENDS

EN388	MECHANICAL HAZARDS
	PERFORMANCE LEVELS (X = NOT TESTED)
3 1 1 1 A	
0-4 0-5 0-4 0-4 A-F P	
	Impact protection (optional)
	Cut resistance according to ISO 13997
	Puncture resistance
	Tear resistance
	Blade cut resistance
	Abrasion resistance

EN407	THERMAL RISKS (HEAT AND FIRE)
	PERFORMANCE LEVELS (X = NOT TESTED)
X 1 X X X X	
0-4 0-4 0-4 0-4 0-4 0-4	
	Resistance to large quantities of molten metal
	Small splashes of molten metal
	Radiant heat resistant
	Convective heat resistance
	Contact heat resistance
	Limited flame spread

EN ISO 374-1	CHEMICAL RISKS
	A: Methanol J: n-Heptane K: Sodium hydroxide 40% L: Sulphuric acid 96% O: Ammonia 25% P: Hydrogen peroxide 30% T: Formaldehyde 37%
TYPE A	
	PROTECTION FROM PESTICIDES
G2	G2: Diluted & concentrated pesticides / Mechanical risk
ISO 18889	
EN ISO 374-5	MICRO-ORGANISMS
	Protection against bacteria and fungi

PRODUCT DETAILS

Interior finish	Textile support Mapa Technology
Exterior finish	Embossed texture
Material	Nitrile
Cuff characteristic	Feston Cuff
Colour	Green
Length (cm)	36
Thickness (mm)	0.95
Sizes	7 8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	7.6E+10 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	2.9E+10 Ω

LOGISTIC DETAILS

Packaging	12 pairs/bag 72 pairs/carton
-----------	---------------------------------

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/08/18/1663
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France