Cut protection

KRYTECH 644

High risk - ISO D



RESICOMFORT TECHNOLOGY

CUT PROTECTION
LEVEL D

EN 388
4X43D

EN 407
X1XXXX

ISO 13997
16 N (1631 g)

Dexterity EN ISO 21420: 5/5

CATEGORY 2

CE

OEKO TEX® STANDARD 100 CQ 979/2 IFTH

High cut protection with comfort, suppleness & breathability without any compromise durability
Can be used with touch devices & touch screen

SPECIFIC ADVANTAGES

Comfort

- A seamless plaited glove for a maximum comfort, dexterity and flexibility while providing optimal cut protection (Cut level ISO D)

Durability

- Extended use guaranteed by our exclusive process RESICOMFORT. Proven breathability, flexibility and durability of the coating.

Skin protection

- Free of harmful substances: OEKO-TEX® STANDARD 100, DMF Free
- Dermatologically approved

Suitable for touchscreen

- Can be used with touch devices & touch screen

Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

Washability

- Washable 1 time at 40°C

Practical

- Cut level easy to identify thanks to the marking on the back of the glove.

INDUSTRIES

- Automotive industry
- Construction industry: Carpenters/Joiners
- Glass industry
- Mining industry

APPLICATIONS

- Strip cutting / Plasma strip cutting
- Handling sheet metal
- Metal working
- Installing steel structures
- Handling glass sheets
- Maintenance with cut risk
- Mechanical maintenance
- Handling of thick metal sheets

Edit 06/11/2026

MAPA SAS capital de 35.000.010 €
420, rue d'Estienne d'Orves
92705 Colombes Cedex France
RCS Nanterre 314 307 720

Cut protection

KRYTECH 644

High risk - ISO D

LEGENDS

EN388 — MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)

4	X	4	3	D	
0-4	0-5	0-4	0-4	A-F	P

- P: Impact protection (optional)
- A-F: Cut resistance according to ISO 13997
- 0-4: Puncture resistance
- 0-4: Tear resistance
- 0-5: Blade cut resistance
- 0-4: Abrasion resistance

EN407 — THERMAL RISKS (HEAT AND FIRE)



PERFORMANCE LEVELS (X = NOT TESTED)

X	1	X	X	X	X
0-4	0-4	0-4	0-4	0-4	0-4

- 0-4: Resistance to large quantities of molten metal
- 0-4: Small splashes of molten metal
- 0-4: Radiant heat resistant
- 0-4: Convective heat resistance
- 1: Contact heat resistance
- X: Limited flame spread

LOGISTIC DETAILS

Packaging	1 pair/bag 12 pairs/bag 48 pairs/carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/11/20/2738
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE

Edit 06/11/2026