Cut protection

KRYTECH 582

High risk - ISO D



GRIP & PROOF TECHNOLOGY

CUT PROTECTION
LEVEL D

EN 388



4X43D

ISO 13997
18 N (1835 g)

Dexterity EN ISO 21420: 5/5

CATEGORY 2

CE

OEKO TEX® STANDARD 100 CQ 979/2 IFTH

Special Grip&Proof nitrile coating provides better liquidproofness and grip in oily situations

SPECIFIC ADVANTAGES

Cut protection
- Optimal cut resistance

Durability
- Excellent abrasion resistance increases glove lifetime

Productivity
- Grip and Proof coating ensures an excellent grip in oily environment. It also reduces muscle strain and boost productivity

Skin protection
- Free of harmful substances: DMF Free

Guaranteed quality
- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

Washability
- Washable up to 5 times at 60°C , allowing to extend glove lifespan, reduce costs and waste.

Practical
- Cut level easy to identify thanks to the marking on the back of the glove.

Care for the environment
- Optimised individual packaging to limit plastic waste
- Recycled material in the packaging: 30 %

INDUSTRIES
- Automotive industry
- Glass industry

APPLICATIONS
- Finishing sharp parts
- Handling metal parts
- Handling sheet metal
- Metal working
- Handling glass sheets
- Rolling, stamping

Edit 31/10/2026

Cut protection

KRYTECH 582

High risk - ISO D

LEGENDS

EN388



MECHANICAL HAZARDS

PERFORMANCE LEVELS (X = NOT TESTED)

4	X	4	3	D	
0-4	0-5	0-4	0-4	A-F	P

- P: Impact protection (optional)
- A-F: Cut resistance according to ISO 13997
- 0-4: Puncture resistance
- 0-4: Tear resistance
- 0-5: Blade cut resistance
- 4: Abrasion resistance

PRODUCT DETAILS

Interior finish	Seamless textile support from HDPE fibres
Gauge	13
Exterior finish	Non-slip grip
Material	Nitrile GRIP&PROOF coating
Cuff characteristic	Knitted Cuff
Colour	Black, Blue
Length (cm)	23-28
Sizes	6 7 8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	5.9E+9 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	4.8E+10 Ω
**Life Cycle Analysis (kg CO2eq)	1.16

**Calculated according to the European PEF methodology (EF 3.1), in accordance with ISO 14040 and ISO 14044. Cradle-to-grave scope, excluding the use phase. LCA data extracted in September 2026. Calculated on the standard reference.

LOGISTIC DETAILS

Packaging	1 pair/bag 12 pairs/bag 48 pairs/carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/12/18/2873
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE

Edit 31/10/2026